



1346-LNSMN

ProxKey III Proximity Access Keyfob - standard keyfob include, 26 bit format, HID logo, printed sequential matching numbering with gaps (Minimum order 100. Always order in



1346-LNSMN

ProxKey III Proximity Access Keyfob - standard keyfob include, 26 bit format, HID logo, printed sequential matching numbering with gaps (Minimum order 100. Always order in

Spécifications techniques

Système

| | |
|-------------------|-----|
| Emplacement carte | Oui |
|-------------------|-----|

Technologie

| | |
|--|--|
| Type d'identifiant | Proximité |
| Fréquence de fonctionnement des cartes et jetons | 125 KHz |
| Technologie 125 KHz supportée | Corporate 1000, EntryProx™, MaxiProx®, MiniProx®, pcProx™, Prox80™, ProxPoint® Plus, ProxPro®, ProxPro® II, ThinLine® II |

Impression

| | |
|--------------------------|-----|
| Impression directe recto | Non |
|--------------------------|-----|

Informations de commande

| | |
|---|-----|
| Quantité minimum par commande | 100 |
| Formulaire de commande de carte spéciale requis | Non |

Caractéristiques physiques

| | |
|----------------------|----------------|
| Matériel | ABS |
| Types de format | Jeton |
| Dimensions physiques | 40 x 32 x 6 mm |
| Poids net | 4 g |
| Couleur | Noir |

Environnement

| | |
|-------------------------------|-------------|
| Température de fonctionnement | -45 to 70°C |
|-------------------------------|-------------|