



FE 160MS

Ventouse supervisée, 600 kg, 12/24v, leds bicolore, montage en applique, dimensions 266 x 73 x 40 mm.

Description

Eco Line magnetic lock, 600 Kgf, monitored, surface mounting

Application

High security applications for internal and external doors. To be mounted inside external doors.

Reliable Security

This state of the art electro-magnetic locking device provides positive, instantaneous door control. Filler plates, angle brackets, and other mounting adapters are available to satisfy a wide range of door and frame types and conditions.

Safe operation

Our locking devices are inherently fail-safe, releasing instantly upon command or loss of power. With no moving parts to wear, stick or bind; no mechanical linkages to bend or break; and no bolt travel time or misalignment to raise concern, both unlocking and locking are always accomplished with ease and efficiency. As those electromagnetic locking devices function independently of any mechanical type locks, magnetic locks will not jeopardize the fire door rating of an opening.



Détails

- 600 Kgf holding power
- Surface mounted
- No residual magnetism
- 12/24 V dc jumper selectable operation
- Monitored changeover
- Mounts easily with a minimum of tools

FE160MS

Ventouse supervisée, 600 kg, 12/24v, leds bicolore, montage en applique, dimensions 266 x 73 x 40 mm.

Spécifications techniques

Général

Type de produit	Verrouillage magnétique
-----------------	-------------------------

Force de maintien

Force de maintien kgf (kilogramme force)	600 kgf
--	---------

Force de maintien N (Newton)	6000
------------------------------	------

Surveillance et statut

Produits supervisés	Oui
---------------------	-----

Témoin LED	Oui
------------	-----

Statut switch de porte	Non
------------------------	-----

Changement surveillé	Oui
----------------------	-----

Capteur de liaison magnétique	Oui
-------------------------------	-----

Électrique

Valeur de l'alimentation	12 / 24 VDC
--------------------------	-------------

Consommation de courant	450 mA (+/- 2,5% @ 13,5 V)
-------------------------	----------------------------

Caractéristiques physiques

Dimensions physiques	266 x 73 x 40 mm (W x H x D)
----------------------	------------------------------

Couleur	Aluminium
---------	-----------
