



IU955

950 Series Intelligent Loop Isolator

General

The IU955 intelligent isolator is designed to protect a 900 series fire detector loop in the event of a short circuit fault. The isolator divides a loop into groups of 20 devices as a rule, so that in the event of a short circuit, no more than 20 devices will be affected and become inoperable.

Design

The IU955 has particularly low non-isolating resistance to allow for more isolators to be installed per loop without affecting the overall cable length of that loop.

Requirement for Isolation

Addressable fire detection systems are normally designed as loops, with the connecting wires starting and finishing at the control panel. Detectors and interfaces are connected at intervals along these cables.

When short circuits occur on a loop, the consequences can be serious, in worst case making the affected loop entirely inoperative. The purpose of isolating circuits is to protect the loop in the event of a short circuit by disconnecting the part of the loop where the short circuit has occurred, thereby isolating the short circuit and only rendering a small part of the loop inoperative. The remainder of the loop continues to function normally. When the short circuit fault has been rectified, the isolating circuitry reconnects the affected section of the loop.

The more isolators that are installed on the loop, the smaller part of the loop is affected by a short circuit condition. By regulation there should never be more than 32 devices between isolators, but it is recommended that isolation is placed at least at every entry and exit point to a zone.



Détails

- No addressing required
- Automatic reset
- Visual "Isolated" indication

IU955

950 Series Intelligent Loop Isolator

Spécifications techniques

Électrique

Tension de fonctionnement 17 to 28 VDC

Isolation

Isolation voltage 13.6 - 14.8 V
Re-connect voltage 12.9 -17.5 VDC
Test current 35 - 50 mA
Isolation current (max) 6.4 mA

Caractéristiques physiques

Dimensions physiques 32 x 100 mm (H x D)

Environnement

Température de fonctionnement -20 to +60°C
Température de stockage -30 to +80°C
Humidité relative 0 to 95% noncondensing
Environnement Intérieur

Régulateur

Certification EN54-17

Electrical

Supply voltage 17 to 28 VDC
Protocol pulses 5 to 9 V
Power up time (max) 10 ms
Continuous loop current (max) 1 A
Short circuit switching (max) 3 A
Quiescent current (max) 45 µA
On resistance (max) 0.2 ohm

Environmental

Operating temperature -20°C to +60°C
Storage temperature -30°C to +80°C
Humidity (no condensation) 0 - 95 % RH

Size (h x d)

32 x 100 mm



En tant que société d'innovation, Carrier Fire & Security se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web fr.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 14 February 2024 - 16:19