

5501-M

Interfaccia per rivelatori di liquidi.

Moisture processor

The 5500 moisture detection series is designed to respond to the presence of water and other non-flammable conductive liquids and to be connected in the closed loop of an alarm system. Two sensors are available; 5505 under carpet sensor and 5515 surface mount sensor. Any combination of up to 4 sensors can be used with the 5501 moisture processor.

The 5501 moisture processor can be used with any closed loop control, dialer or wireless transmitter input circuit. The processor comes with internal lithium batteries that have an anticipated life time of 10 to 15 years. The processor offers flexibility in mounting with no need for an external power source and minimal wiring required.



Dettagli

- Detects presence of water and non-flammable conductive liquids
- No external power required
- Sensor circuit totally isolated by optical couplings
- Up to 4 sensors per 5501 moisture processor

5501-M

Interfaccia per rivelatori di liquidi.

Specifiche tecniche

Generale

Tipo di sensore	Sensore di allagamento
Conessioni	Screw terminals
Contatto allarme	NC, aperto finchè umidità presente
Ritardo allarme	10 s

Cablato / senza fili

Cablato / senza fili	Cablato
----------------------	---------

Elettrico

Batterie	Lithium battery
Durata della batteria	Da 10 a 15 anni

Fisico

Dimensioni fisiche	116 x 70 x 35 mm (L x W x H)
Colore	Marrone

