

# 9-30709

## AirSense Stratos Standalone Command Module

### Description

---

AirSense Stratos Command Module provides a single location display, control and interfacing option for systems of upto 127 detectors. Command Module allows global programming of all detector functions simultaneously.

The integral bargraph automatically displays the status of the detector with the highest alarm level to identify potential problem areas.

The PIN protected programmer enables global entry of all detector settings to significantly reduce commissioning time.

### Typical Applications

---

- Data storage units
- Prison cells
- Plant rooms
- Air conditioning units
- Equipment racks
- Computer rooms
- Air duct protection
- Heritage property protection
- Critical equipment
- Anti-smoking enforcement
- Motor rooms

### Options Available

---

- Addressable Protocol Interface Cards APIC™ available
- SenseNet compatible - up to 127 detectors per loop
- Remote Display units available
- Suitable for MatrixScan, a patented software system which provides virtual addressable location detection - e.g. 10 physical detectors would provide up to 45 unique addressable locations.



### Dettagli

---

- RS485 communications built in as standard for networking and remote communications
- Network control of 127 detectors
- Built in Short Isolators for optimum reliability

# 9-30709

## AirSense Stratos Standalone Command Module

### Specifiche tecniche

---

#### Generale

---

Indicazione stato	LED and LCD
Interfaccia utente	Keypad

---

#### Elettrico

---

Tensione di esercizio	21.6 to 26.4 VDC
Consumo attuale	250 mA

---

#### Uscita

---

Quantità in uscita	5 - Pre-Alarm, Alarm, Alarm2, Aux Alarm (n/o) and Fault (n/c)
--------------------	---

---

Tipo di uscita e intervallo 500 mA @ 30 V

---

#### Fisico

---

Physical dimensions	427 x 372 x 95 mm (W x H x D)
Peso netto	5.2 kg
Colore	Crema
Tipo di montaggio	Montaggio a parete
Cavo di entrata	6 x M20
Materiale (scatola)	Lamiera d'acciaio

---

#### Ambientale

---

Temperatura operativa	-10 to +60°C (EN54-20)
Umidità relativa	0 to 90% noncondensing
Ambiente	Interno
IP rating	IP40

---



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita [it.firesecurityproducts.com](http://it.firesecurityproducts.com) online o contatta il tuo riferimento commerciale.

Last updated on 7 March 2024 - 11:23