

AS964WI

Avvisatore acustico serie 950, con isolatore incorporato multi tono autoalimentato dal loop. Protezione IP65. Colore bianco. EN54-3, EN54-17 CPD

General

The AS964WI is a 950 series, intelligent loop powered open-area sounder in WHITE with a built in isolator. It is designed for use in indoor and outdoor open area applications. It supports 3 tones with two volume settings.

A locking mechanism is available to prevent unauthorized removal of the AS964WI from its base.

Isolation and Maintenance

The AS964WI sounder is supplied with an isolating base. A yellow LED on the base is illuminated if a loop short circuit is detected. All fault and abnormal conditions such as sounder failures are reported back to the panel for easy faultfinding.

Sounder Tone Support

That AS964WI supports the following tones:

- Standard
- Slow Whoop (NEN2575)
- DIN (33404pt3)

Two volume settings are available in each tone variant.



Dettagli

- Self-test fault monitoring
- Multiple tones
- Alarm synchronisation
- Loop powered
- Including loop isolator

AS964WI

Avvisatore acustico serie 950, con isolatore incorporato multi tono autoalimentato dal loop. Protezione IP65. Colore bianco. EN54-3, EN54-17 CPD

Specifiche tecniche

Elettrico

Tensione di esercizio	17 to 28 VDC
Consumo attuale	5 mA @ 24 VDC (Alarm, sounder only) <1.2 mA @ 24 VDC (Switch on surge, <1 s) <333 µA @ 24 VDC (Quiescent)

Sirena

Livello di uscita	100 dB(A) max. @ 90° (± 3dB(A))
Frequenza	Tone dependant

Ambientale

Ambiente	All'aperto
IP rating	IP65

Regolatorio

Certificazioni	EN54-17, EN54-3
----------------	-----------------