

ATS1190X4

ATS1190 Confezione da 4 pezzi

Product Overview

The ATS1190X4 is an economic 4 pack of ATS1190 smart card readers. The reader connects directly on the RS485 data bus of the control panel or 4-Door Controller and may be configured and addressed via a LCD keypad. Some security options (Site code & 4-byte security code) are only programmable via TITAN and configuration cards. The ATS1190 is supplied standard with a white removable dress cover, which can be interchanged with one of four other colours available (see Ordering Information).

High quality cards & key fobs

Both the smart chip and antenna are embedded inside the cards & fobs. Printing is possible on the cards using any industry standard printer. The ATS1472 cards feature a programmable magnetic stripe for Time & Attendance or other applications.

Security Features

The ATS smart card technology has the ability to program a unique 268 million, 4-byte, combination security code (values from 0 through 127 are applicable for EMEA). This allows the memory card to unlock/open/disarm based on three keys; the card number, the Site code and the 4-byte security code. Once a 4-byte security code has been created, downloaded to the programmer and the cards, it is not possible to read the memory on the card or even recognise the card memory at any other reader or TITAN and programmer combination. Communications between TITAN and the programmer may also be password protected to prevent the 4-byte security code from being uploaded from the programmer into another PC running TITAN.

Read/Write Encryption

The ATS Smart card technology also features an exclusive read/write encryption. When a card is presented at a reader, data are downloaded into the reader, encrypted and re-written back into the card. The readers can also be configured to operate in stand-alone or connected to control devices like office equipment or vending machines. This function enables credits to be assigned on user cards and deducted by the readers, purely on a usage basis. Up to 65535 credits may be allocated in up to 4 different banks with 16 access levels and 4 locations. The reader determines of which bank credits have to be deducted and the number of credits per valid presentation.

Multiple Card Badging

The ATS smart card readers can be used for arming/disarming areas as well as for access applications. It is suitable for using the multiple card badging techniques which are available for the advisor MASTER control panel family. A user could arm the system in the evenings by badging his card three times within 10 seconds interval. Another application could be for doors which can be programmed so that badging once unlocks, badging twice with the same card keeps the door unlocked to allow people in and out without card, and badging



Dettagli

- Compatibile con le centrali Everon e Advisor Advanced
- Confezione da 4 pezzi

three times re-locks the door.

ATS1190X4

ATS1190 Confezione da 4 pezzi

Specifiche tecniche

Sistema

Distanza di lettura	6 to 8 cm
Distanza massima lettori da centrale	1.5 km
Tipo di tessere supportate	HiTag2
Tipo di indirizzamento	Indirizzamento tessere, Indirizzamento tastiere, Indirizzamento software
No. di LEDs	Tricolor
No. di cover inclusi	4, White
Accessori lettori	Cover colorate opzionali

Tecnologia

Tipo di lettore	Prossimità, Smart Card
Frequenza di trasmissione operativa del lettore	125 KHz
Tecnologia supportata	HiTag 2 125 KHz

Interfaccia e connessioni

Interfaccia	ATS RS-485, Wiegand
Tipo di connettore	Codino
Lunghezza cavo	250

Ingressi / Uscite

Ingressi	Richiesta di uscita
Uscite	1 Open Collector (25 mA)

Tipo Manomissione

Tamper Anti-rimozione	Si
-----------------------	----

Operazioni

PIN tastiera	No
--------------	----

Elettrico

Tensione di esercizio	9 to 14 VDC
Consumo attuale	25 mA typical 80 mA max.

Fisico

Dimensioni fisiche	36 x 110 x 20 mm
Peso netto	200g (per reader)
Colore	Bianco
Materiale	Plastica
Tipo di montaggio	Montaggio a superficie

Ambientale

A prova di vandalo	No
Temperatura operativa	-35 to +66°C
Ambiente	Interno
IP rating	IP54



In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 18 June 2026 - 14:24