

DB951

Base per isolatore di linea

DP 951 Optical Smoke Monitor

The DP 951 optical smoke monitor has an internal pulsing LED and a photo-diode at an obtuse angle. In clear air conditions the photo-diode in the monitor receives no light from the LED and produces a corresponding analogue signal. This signal increases when smoke enters the chamber and light is scattered onto the photodiode. The signal is processed by the electronic circuitry and transmitted to the control equipment in exactly the same way as in the case of the ionisation smoke monitor.

DT 952 Temperature Monitor

The device monitors temperature by using a single thermistor network which provides a voltage output proportional to the external air temperature. The voltage signal is processed and transmitted to the control equipment in the same way as in the case of the ionisation smoke monitor.

Isolators

Isolators are designed to protect the detector or loop in the event of a short circuit fault. They divide a loop of fire monitors and ancillary devices into groups, so that, in the event of a short circuit, no more than just that group or detector will be inoperable.

Unique Addressing

A unique, patented addressing method provides simple, user-friendly and accurate identification of monitor location whereby a coded card, inserted in the base, is read by any monitor as it is plugged in. All the electronic components are in the monitor, but the location information is held in the base. Addressing errors during maintenance and service are eliminated. Precoded and pre-numbered address cards are also available. These address cards simplify and speed up installation and commissioning.



Dettagli

- Base indirizzata passiva
- Indirizzamento tramite linguetta codificata
- Estetica armoniosa
- Approvata EN 54, BOSEC, VdS, CNBOP

DB951

Base per isolatore di linea

Specifiche tecniche

Generale

Indicazione stato	No remote indicator facility
-------------------	------------------------------

Elettrico

Terminali	4
-----------	---

Fisico

Dimensioni fisiche	100 x 10 mm (Ø x H)
--------------------	---------------------

Ambientale

Ambiente	Interno
----------	---------

Regolatorio

Certificazioni	EN54-17
----------------	---------



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 14 February 2024 - 16:38