

DM860

MCP Red, Manual Fire Alarm

General

The DM860 is a RED, type-B, dual action manual call point for surface mount applications.

Construction

The rugged aluminum housing, combined with a fade resistant coating, guarantees a long lasting high quality product. The revolving door, with an opening angle of 180°, contains an interchangeable break glass.

The revolving door also contains a special clip that features as a failsafe to prevent the door from being closed while the unit is still triggered.

Dual action

The DM860 is defined as a type-B, dual action manual call point due to the fact that two actions are required to trigger the manual call point. First the break glass must be broken, and secondly the button must be pushed.



Dettagli

- Robust aluminium housing
- Type B / Dual action
- Surface mount

DM860

MCP Red, Manual Fire Alarm

Specifiche tecniche

Fisico	
Physical dimensions	125 x 125 x 34 mm (W x H x D)
Peso netto	400 g
Colour	Rosso
Ambientale	
Operating temperature	-20 to +60°C
Ambiente	Interno
IP rating	IP43
Regolatorio	
Certification	EN54-11
Series resistor	
	1000 ohm or user defined
Boîtier	
	Aluminum
Dimensions	
	125 x 125 x 34 mm
Weight	
	400g
Colour	
	Red
Operating Temperature	
	-20°C to +60°C
IP Rating	
	IP43



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.