

GS300

Sensore piezo rottura vetri mini con memoria.

High Performance

The glassbreak detector GS300 is designed to detect the specific ultrasonic frequency range produced by breaking glass. Knocks and other normal disturbances to a windowpane do not trigger an alarm. Suitable for use on standard window glass or plate glass the GS300 provide a 2 meter radius of protection. The detector may be fitted as close as 2 cm from the window frame and still provide a full 2 metre radius of coverage on standard glass. The detector is moulded into a plastic housing and delivered with 2m cable as a standard (exists also in 6 & 20 meters). They are featuring a built-in latch LED indicator for easy location of alarmed detectors.



Dettagli

- Small and unobtrusive
- Latching alarm indication
- 2m radius protection
- Easy to install
- No adjustment
- Tamper proof

GS300

Sensore piezo rottura vetri mini con memoria.

Specifiche tecniche

Generale

Tecnologia	Piezo
Tipo di vetro	Piato
Gamma	2 m radius
Interruttore antimanomissione	No

Cablato / senza fili

Cablato / senza fili	Cablato
----------------------	---------

Elettrico

Valore di alimentazione	3 to 16 VDC
Consumo attuale	4 mA @ 6 VDC 9 mA @ 12 VDC

Fisico

Dimensioni fisiche	37 x 19 x 12 mm
Peso netto	50 g
Colore	Bianco
Tipo di montaggio	Montaggio a superficie

Ambientale

Temperatura operativa	-25 to +70°C
IP rating	IP67

Regolatorio

Certificazioni	EN50131 Grade 2, VdS
----------------	----------------------