

IU955

Isolatore di linea

General

The IU955 intelligent isolator is designed to protect a 900 series fire detector loop in the event of a short circuit fault. The isolator divides a loop into groups of 20 devices as a rule, so that in the event of a short circuit, no more than 20 devices will be affected and become inoperable.

Design

The IU955 has particularly low non-isolating resistance to allow for more isolators to be installed per loop without affecting the overall cable length of that loop.

Requirement for Isolation

Addressable fire detection systems are normally designed as loops, with the connecting wires starting and finishing at the control panel. Detectors and interfaces are connected at intervals along these cables.

When short circuits occur on a loop, the consequences can be serious, in worst case making the affected loop entirely inoperative. The purpose of isolating circuits is to protect the loop in the event of a short circuit by disconnecting the part of the loop where the short circuit has occurred, thereby isolating the short circuit and only rendering a small part of the loop inoperative. The remainder of the loop continues to function normally. When the short circuit fault has been rectified, the isolating circuitry reconnects the affected section of the loop.

The more isolators that are installed on the loop, the smaller part of the loop is affected by a short circuit condition. By regulation there should never be more than 32 devices between isolators, but it is recommended that isolation is placed at least at every entry and exit point to a zone.



Dettagli

- No addressing required
- Automatic reset
- Visual "Isolated" indication

IU955

Isolatore di linea

Specifiche tecniche

Elektrico

Tensione di esercizio 17 to 28 VDC

Fisico

Dimensioni fisiche 32 x 100 mm (H x D)

Ambientale

Temperatura operativa -20 to +60°C

Temperatura di immagazzinamento -30 to +80°C

Umidità relativa 0 to 95% noncondensing

Ambiente Interno

Regolatorio

Certificazioni EN54-17

Electrical

Supply voltage 17 to 28 VDC

Protocol pulses 5 to 9 V

Power up time (max) 10 ms

Continuous loop current (max) 1 A

Short circuit switching (max) 3 A

Quiescent current (max) 45 µA

On resistance (max) 0.2 ohm

Isolation

Isolation voltage 13.6 - 14.8 V

Re-connect voltage 12.9 - 17.5 VDC

Test current 35 - 50 mA

Isolation current (max) 6.4 mA

Environmental

Operating temperature -20°C to +60°C

Storage temperature -30°C to +80°C

Humidity (no condensation) 0 - 95 % RH

Size (h x d)

32 x 100 mm



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 14 February 2024 - 16:19