

S35-2MLC

SFP-Port 1000Base-SX Mini-GBIC Module - 2 Fiber - 550m - Multi-Mode - 850nm (-40~75°C) - Based on 50/125µm OM2 Fiber

Overview

The KGS Fire & Security transceiver module is specifically designed to accommodate high-performance optical fiber. Compliant with the SFP Multisource Agreement (MSA), these transceiver modules feature hot-plug capability for easy installation without interrupting host equipment operating online. The SFP Mini GBIC transceiver can install into KGS Fire & Security switch products with 100Base-FX or 1000Base-SX/LX SFP interface.



Dettagli

- SFP multi-source agreement compliant
- Data rate 1.25 Gbps
- Max 220 m distance based on 62.5 / 125 (OM1) fiber
- Max 550 m distance based on 50 / 125 (OM2) fiber
- Class 1 laser safety standard IEC 60825 compliant
- LC duplex receptacle
- Low power dissipation
- Plug-and-play capability for easy installation
- Hot Pluggable
- -40 to +75°C operation temperature
- TTL signal detect indicator
- Single power supply 3.3 V
- Comply with the IEEE 802.3ab

S35-2MLC

SFP-Port 1000Base-SX Mini-GBIC Module - 2 Fiber - 550m - Multi-Mode - 850nm (-40~75°C) - Based on 50/125µm OM2 Fiber

Specifiche tecniche

Generale

Categoria	SFP
Tipo porta	Modo Multi
No. di fibre	2
Velocità porta	Gigabit
Lunghezza d'onda	850 nm
Distanza massima	550 m

Elettrico

Tensione di esercizio	3.3 VDC
-----------------------	---------

Fisico

Dimensioni fisiche	59 x 15 x 12.4 mm (W x D x H) 2.20 x 0.59 x 0.49 in. (W x D x H)
Peso netto	18 g 0.6 oz

Ambientale

Temperatura operativa	-40 to 75°C
Temperatura di immagazzinamento	-40 to 85°C
Umidità relativa	5 to 95% noncondensing

General

Connector	LC
Data rate	1.25 Gbps
PHY type	1000Base-SX
Reliability (MTBF)	>50,000 hrs @ 25°C

Transmitter Electro-Optical Interface

EMI	EN 55022 CLASS A:2006+A1 : 2007 / EN61000-3-2:2006 / EN61000-3-3: 1995+A1:2001+A2:2005
Optical output power	Min. : -9.5 dBm, Type : - , Max. : -4 dBm
Power budget	7.5
Receiver	-17 dBm

Electrical

AS/NZS CISPR 22	2006
-----------------	------

Regulatory

	IEEE 802.3ab Fast Ethernet Standard
	Class 1 laser product complies with EN 60825-1

