

S40-2MLC

SFP+ Port 10BaseG-SR SFP+ - 2 Fiber - 300m - Multimode Mode (OM3 Fiber) - 850nm (0~70°C)

Overview

The KGS Fire & Security transceiver module is specifically designed to accommodate high-performance optical fiber, including integrated duplex data link over single mode.

The S40-2MLC transceiver module features hot-plug capability for easy installation without interrupting host equipment operating online. The SFP+ transceiver module can install into KGS Fire & Security switch products with 10GBase-SR SFP+ interface.



Dettagli

- Flexible SFP+ package
- Complies with the IEEE 802.3ae 10 Gigabit Ethernet Standard
- Class 1 laser safety standard IEC 60825 compliant
- LC duplex receptacle
- Low power dissipation
- Plug-and-play capability for easy installation
- Hot Pluggable
- 0°C to +70°C operation temperature
- TTL signal detect indicator
- Single power supply 3.3V

S40-2MLC

SFP+ Port 10BaseG-SR SFP+ - 2 Fiber - 300m - Multimode Mode (OM3 Fiber) - 850nm (0~70°C)

Specifiche tecniche

Generale

Categoria	SFP
Tipo porta	Modo Multi
No. di fibre	2
Velocità porta	10G
Lunghezza d'onda	850 nm
Distanza massima	300 m

Elettrico

Tensione di esercizio	3.3 VDC
-----------------------	---------

Fisico

Dimensioni fisiche	59 x 15 x 12.4 mm (W x D x H) 2.20 x 0.59 x 0.49 in. (W x D x H)
Peso netto	18 g 0.6 oz

Ambientale

Temperatura operativa	0 to 70°C
Temperatura di immagazzinamento	-40 to 85°C
Umidità relativa	5 to 95% noncondensing

Regolatorio

Conformità	CE, FCC
------------	---------

General

Reliability (MTBF)	>50,000 hrs @ 25°C
--------------------	--------------------

Transmitter Electro-Optical Interface

EMI	EN 55022 CLASS A:2006+A1 : 2007 / EN61000-3-2:2006 / EN61000-3-3: 1995+A1:2001+A2:2005
Optical output power	-7.0 dBm (avg.)
Power budget	7 dB

Regulatory

Class 1 laser product complies with EN 60825-1
--

