SMA-L-PROX

MA SIGMA Lite - Prox, Multi-factor Bio/Card, HID Prox, 500 users, IP65, CE

MA SIGMA Lite & MA SIGMA Lite Plus Series

Engineered with the same attention to detail and performance as their predecessor, the MorphoAccess® SIGMA Lite terminals are specifically designed to equip narrow mounting surfaces, such as glass/aluminum door mullions, turnstiles or server rack doors. With two designs (with touchscreen: MA SIGMA Lite Plus ; without touchscreen: MA SIGMA Lite) and multiple embedded card reader options, there are a variety of models to address the widest range of deployment scenarios, both indoor and outdoor.

Embedded web server

The MA SIGMA Lite Series enables on-device enrollment, terminal configuration and transaction log retrieval thanks to the embedded web server. Moreover, it can be used with any device (PC, laptop, tabled, smartphone), any operating system (Windows, Android, iOS) or any web browser (Google Chrome, Mozilla Firefox, Safari and Internet Explorer).

Enhanced interactivity

Thanks to the 2.8” QVGA touchscreen on the MA SIGMA Lite Plus Series, you can benefit from an enhanced user experience. The MA SIGMA Lite Plus holds T&A in and out function keys, User ID/PIN/BioPin management and intuitive icons and live messages.

Compatible with existing installations

The MA SIGMA Lite Series can be used to upgrade an existing installation or to complement the installation with MorphoAccess® SIGMA (Lite) devices using the MorphoManager application or MIK SDK on a Morpho network or the SecureAdmin™ application or SecureSDK™ on a BioScrypt network.

Enhanced security features

The MA SIGMA Lite Series encompasses the latest and greatest anti-fraud features, such as: fake finger detection, duress finger, timed anti-pass back function and banned/authorized user lists.

Dettagli

- Leading fingerprint technology inside - 1:10,000 user identification in 1 second
- High capacity - 30,000 templates, 250,000 IDs in authorized user list, 1 million logs
- Advanced anti-fraud features
- Flexibility - Optional Prox, iCLASS or MIFARE/DESFire contactless card reader
- Tough design - IP65 rated and vandal resistant (IK08, SIGMA Lite only)

SMA-L-PROX

MA SIGMA Lite - Prox, Multi-factor Bio/Card, HID Prox, 500 users, IP65, CE

Specifiche tecniche

Sistema

Distanza massima lettori da centrale	Ethernet: 100 m, RS485: 1219 m
RTE (richiesta di uscita)	No
CSN (Numero di serie della carta)	Si
Modello personalizzato	No
No. di LEDs	1

Tecnologia

Tipo di lettore	Biometrico
Frequenza di trasmissione operativa del lettore	125 KHz
Tecnologia supportata 125 KHz	HID Prox

Biometrico

Tipo biometrico	Fingerprint
Tipo di sensore biometrico	Ottica

Interfaccia e connessioni

Interfaccia	Ethernet, OSDP V2, OSDP V2 Secure Channel, RS-485, USB, Wiegand
Tipo di connettore	Rete, Codino
Lunghezza cavo	40 cm

Tipo Manomissione

Tamper Anti-rimozione	No
Tamper di apertura	Si

Operazioni

Autonomo	Si
PIN tastiera	No

Elettrico

Tipo di alimentatore	VDC
Valore di alimentazione	12 to 24 VDC

Fisico

Peso netto	280 g
Peso spedizione	325 g
Colore	Nero
Materiale	Policarbonato
Fattore di forma	Sovradimensionato
Tipo di montaggio	Montaggio a superficie

Ambientale

A prova di vandalo	No
Temperatura di immagazzinamento	-10 to +55°C

Regolatorio

Conformità	CE, FCC, REACH, RoHS

The latest product specifications can be located at www.lenels2.com or by contacting your sales representative.
LenelS2 reserves the right to change product specifications without prior notice.

Last updated on 21 May 2024 - 16:53