

TVGP-M01-0403-PTZ-G

**Dome PTZ IP Truvision 4MPX, 32X, IR 200m
, Hi-PoE/24VAC, Staffa a muro Inclusa.**

Overview

TVGP-M01-0403-PTZ-G is a Pan Tilt Zoom IP camera for use in both indoor and outdoor installations. The camera's 4 megapixel resolution combined with excellent low light capabilities, 32x optical zoom and 200m IR illumination ensures you capture the required level of detail at all times.

The camera is fully programmable, with up to 300 presets along with 8 patrol and preset tours.

The 8-zone privacy mask feature allows these cameras to block out sensitive areas. In addition, the variety of intelligence features and analytics adds substantial value and enhanced performance to any video system.

Video intelligence

The camera comes with a various built-in intelligent video features like line crossing detection, intrusion zone detection, region entry/exit detection and more. Some of these intelligence features can be refined further by adding person/vehicle classification to filter out unwanted events which automatically results in more efficient alarm event and storage management.

Technology

The camera features H.265+ compression to optimize its bandwidth and storage requirements. At the same time, H.264 which is also supported, allows the camera to be connected to legacy installations where needed.

ONVIF, PSIA and CGI command sets ensure that this camera can also be easily connected to virtually any video surveillance system.



Dettagli

- 4MP resolution
- 32x optical zoom, 16x digital zoom
- IR illumination up to 200 m
- Video intelligence with person/vehicle classification options
- Built-in speaker for audio alarms
- Flashing white alarm LED
- H.265+ compression
- Wall mount bracket included

TVGP-M01-0403-PTZ-G

Dome PTZ IP Truvision 4MPX, 32X, IR 200m , Hi-PoE/24VAC, Staffa a muro Inclusa.

Specifiche tecniche

Generale

Tecnologia	IP
Standard Video	NTSC, PAL
OSD	Text Overlay
Mascheramento della privacy	24 programmable polygon privacy masks, mask color or mosaic configurable
Compatibilità Software	TruVision Navigator, TVRmobile, Web Browser

Telecamera

Dimensioni del sensore	1/1.8"
Risoluzione Max.	4 MP
Scansione del sensore	Progressive
Tipo di sensore	CMOS
Tempo di scatto	1/1 to 1/30,000 s

Prestazioni di illuminazione

Tipo WDR	True WDR
WDR	120 dB
Giorno / notte	True Day/Night
Rimozione del filtro IR motorizzata	Si
Sensibilità del colore	Color: 0.005 Lux @ (F1.5, AGC ON), B/W: 0.001 Lux@(F1.5, AGC ON), 0 Lux with IR
Infrarosso (IR)	Si
Portata IR	200 m
Lunghezza d'onda IR	850nm

Codifica

Flussi video	3
Compressione flusso principale	H.264, H.264+, H.265, H.265+
Compressione flusso secondario	H.264, H.265, MJPEG
Compressione del terzo flusso	H.264, H.265, MJPEG
Velocità in bit video	32 to 16 Mbps
Risoluzione flusso principale	1280 x 720 (XVGA), 1280 x 960 (720p), 1920 x 1080 (1080p), 2560 x 1440
Risoluzioni flusso secondario	352 x 288 (CIF), 640 x 480 (VGA), 704 x 576 (4CIF)
Risoluzione del terzo flusso	1280 x 720 (XVGA), 1280 x 960 (720p), 1920 x 1080 (1080p), 352 x 288 (CIF), 640 x 480 (VGA), 704 x 576 (4CIF)
Risoluzione Max. @ fps	2560 x 1440 @ 25 fps

Lente

Lunghezza focale	5.9 mm to 188.8 mm - Horizontal FoV 50.8 to 2.6°, vertical FoV 29.4 to 1.5°, Diagonal FoV 57.4 to 3°
f-stop	Max. F1.6
Diaframma automatico	Si
Messa a fuoco automatica	Si
Zoom motorizzato	Si

Pan / tilt / zoom

Pan	Pan speed: configurable from 0.1° to 160°/s; preset speed: 240°/s
Inclinare	Tilt speed: configurable from 0.1° to 120°/s, preset speed 200°/s
Pan infinito	Yes
Automaattinen kääntö	Si
Zoom ottico	32x
Zoom digitale	16x
Posizioni preset	300
Tour preimpostati	8
Shadow tours	4

Rete

Interfaccia di rete	RJ-45 10/100 Mbps self-adaptive Ethernet interface
Integrazione	CGI, ISAPI, ONVIF Profile G, ONVIF Profile S, ONVIF Profile T, SDK
Protocolli di rete supportati	802.1x, Bonjour, DDNS, DHCP, DNS, ezDDNS, FTP, HTTP, HTTPS, ICMP, IGMP, IPv4, IPv6, NTP, PPPoE, RTCP, RTP, RTSP, SNMP, TCP/IP, UPnP

Audio

Compressione audio	G.711a, G.711alaw, G.711ulaw, G.722.1, G.726, MP2L2, PCM
Ingresso audio	1 input (line in), max. input amplitude: 2-2.4 vpp, input impedance: 1 kΩ ± 10%
Uscita audio	1 output (line out), line level, output impedance: 600 Ω and built-in speaker
Bitrate audio	64 Kbps (G.711)/16 Kbps (G.722.1)/16 Kbps (G.726)/32-192 Kbps (MP2L2)

Allarme I/O

Ingresso di allarme	2
Uscita di allarme	1 alarm output and white flash alarm LED

Memoria

Tipo di archiviazione locale	Built-in memory card slot, support microSD/SDHC/SDXC card
Capacità Max. di registrazione	256 GB

TVGP-M01-0403-PTZ-G

Dome PTZ IP Truvision 4MPX, 32X, IR 200m
, Hi-PoE/24VAC, Staffa a muro Inclusa.

Intelligenza video

Attivazione allarme	HDD error, HDD full, Invalid login, Conflitto di indirizzi IP, Rete disconnessa
ROI	8 fixed regions for each stream
Analisi video	Rilevazione Audio exception, Face capture, Intrusion detection, Rilevazione Line crossing, Motion detection, Rilevazione oggetto rimosso, Rilevazione entrata in regione, Rilevazione uscita da regione, Rilevazione di bagagli incustoditi
Opzioni di intelligence	Face capture: can detect up to 5 faces simultaneously. Supports detecting, capturing, grading, selecting of faces in motion, and generates the best face picture. Person/vehicle filtering: these options can be configured on line crossing, intrusion detection, region entry/exit detection.
Tracking intelligente	Si

Elettrico

Tensione di esercizio	24VAC, Hi-PoE
Consumo di energia	Max. 42 W (including max. 18 W for IR and max. 10 W for heater)

Fisico

Dimensioni fisiche	Ø 220 × 363.3 mm Ø 8.66 × 13.91 in.
Peso netto	Approx. 5.0 kg Approx. 11.03 lb.
Colore	Grigio (Pantone 428c)
Materiale	Alluminio
Form Factor	PTZ
Montaggio	Corner mount (requires additional accessory), Montaggio a pendente, Pole mount (requires additional accessory), Montaggio a parete

Ambientale

Temperatura operativa	-30 to 65 °C -22 to 149 °F
Umidità relativa	90% or less non-condensing
IP rating	IP66

Regolatorio

Conformità	CE, EMC, FCC, RCM, REACH, RoHS 3, UKCA, UL, WEEE
------------	--

General

Plugin-free web browser support	Google Chrome, Mozilla Firefox
---------------------------------	--------------------------------

Network

Simultaneous live view	Up to 20 channels
------------------------	-------------------

Compatible accessories


Wall mount bracket	Included
--------------------	----------

Environmental

Impact rating	IK10 (excluding glass window part)
---------------	------------------------------------

Prodotti compatibili

Categoria	Riferimento	Descrizione
Staffe e Supporti	TVMI-PM	
Staffe e Supporti	TVMI-PM2	
Staffe e Supporti	TVMI-PM3	
Staffe e Supporti	TVP-CMB-01	
Staffe e Supporti	TVP-PMB-01	
Staffe e Supporti	TVP-WM-CM	Staffa per fissaggio ad angolo per dome TruVision analogiche ed IP, da utilizzare con la staffa TVP-WMB.
Staffe e Supporti	TVP-WM-PM	Staffa per fissaggio a palo per dome PTZ della linea TruVision analogiche ed IP, da utilizzare con la staffa TVP-WMB.



In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 21 January 2026 - 20:00