

TVP-2401

TruVision HD-TVI Analog PTZ, 1080P, 30X, DWDR, Wall Mount, CVBS & TVI Dual-Output, TVI/RS485/RS422 Control, 24VAC, IP66, PAL.

Overview

The TruVision HD-TVI Analog PTZ Cameras by Interlogix® utilize the latest PTZ technology to provide powerful, cost-effective surveillance for retail, commercial and small business applications. With 1080p resolution and a 30X optical zoom (16X digital) working together, these cameras deliver crisp, clear images, even at a distance.

With advanced features, such as True Day/Night surveillance and Digital Wide Dynamic Range (DWDR) imaging, these cameras provide optimal image quality in a variety of indoor or outdoor environments. HD-TVI Analog PTZ cameras are easy to change, with wall, pendant, surface or flush mounting options to meet various application needs.

These cameras are also fully programmable, with up to 256 presets, 8 preset tours, and shadow tours for end-user customization and flexibility. A 24-zone privacy-mask feature allows these cameras to block out sensitive areas, such as fitting rooms, or restricted areas. Motion detection, auto tracking, privacy masking and electronic image stabilization add substantial value and enhanced security to any surveillance system.



Dettagli

- 1/3" Progressive Scan CMOS
- 1080p resolution
- Dual output HD-TVI and 960H BNC
- HD-TVI technology for transmitting full HD-quality video over existing coax cable
- 24 Privacy Masks
- Models include 2 alarm inputs and 1 relay output
- 256 preset positions, 8 preset tours, and 4 shadow tours
- 360° Endless Rotation
- 250°/s Pan Preset Speed and 300°/s Tilt Preset Speed
- Auto-Flip image
- Compatible with GEA and UVP accessories
- Wall bracket to be ordered separately
- EIS (Electronic Image Stabilization)

TVP-2401

Truvision HD-TVI Analog PTZ, 1080P, 30X, DWDR, Wall Mount, CVBS & TVI Dual-Output, TVI/RS485/RS422 Control, 24VAC, IP66, PAL.

Specifiche tecniche

Generale

Tecnologia	HD-TVI analogico
Standard Video	PAL
Uscita video	HD-TVI

Telecamera

Dimensioni del sensore	1/3"
Risoluzione Max.	1080p
Scansione del sensore	Progressive
Tipo di sensore	CMOS

Prestazioni di illuminazione

Tipo WDR	Digital WDR
Giorno / notte	True Day/Night
Rimozione del filtro IR motorizzata	Si
Infrarosso (IR)	No

Lente

Tipo obiettivo	Varifocale motorizzata
Tip di montaggio obiettivo	Camera Block
Diaframma automatico	Si
Messa a fuoco automatica	Si
Zoom motorizzato	Si

Pan / tilt / zoom

Automaattinen kääntö	Si
Zoom ottico	30x
Zoom digitale	16x
Protocolli PTZ supportati	AD_CODE, BOSCH_CODE, Interlogix RS-485, Pelco-D, Pelco-P

Allarme I/O

Ingresso di allarme	2
---------------------	---

Memoria

Supporto registrazione locale	No
-------------------------------	----

Intelligenza video

Attivazione allarme	Rivelatori di movimento, Privacy Masking, Video tampering
Analisi video	Defog, Stabilizzazione elettronica dell'immagine
Tracking intelligente	No

Elettrico

Tipo di alimentatore	24 VAC
----------------------	--------

Fisico

Colore	Grigio
Form Factor	PTZ
Montaggio	Montaggio a pendente, Wall mount (requires additional accessory)

Ambientale



A prova di vandalo	Si
Valutazione impatto	IK10
Ambiente	All'aperto

Regolatorio

Conformità	CE, FCC, HALT, REACH, RoHS, UL, WEEE
------------	--------------------------------------

Prodotti compatibili

Categoria	Riferimento	Descrizione
Alimentatori	ATD-6814-PSU	Alimentatore per CyberDome, Legend Dome, UltraView PTZ, 24Vca 4A in contenitore da esterno.



Unit: mm



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 26 January 2024 - 10:13