

# 9-30624

## AirSense Stratos Standalone Command Module

### Description

---

AirSense Stratos Command Module provides a single location display, control and interfacing option for systems of upto 127 detectors. Command Module allows global programming of all detector functions simultaneously.

The integral bargraph automatically displays the status of the detector with the highest alarm level to identify potential problem areas.

The PIN protected programmer enables global entry of all detector settings to significantly reduce commissioning time.

### Typical Applications

---

- Data storage units
- Prison cells
- Plant rooms
- Air conditioning units
- Equipment racks
- Computer rooms
- Air duct protection
- Heritage property protection
- Critical equipment
- Anti-smoking enforcement
- Motor rooms

### Options Available

---

- Addressable Protocol Interface Cards APIC™ available
- SenseNet compatible - up to 127 detectors per loop
- Remote Display units available
- Suitable for MatrixScan, a patented software system which provides virtual addressable location detection - e.g. 10 physical detectors would provide up to 45 unique addressable locations.



### Details

---

- RS485 communications built in as standard for networking and remote communications
- Network control of 127 detectors
- Built in Short Isolators for optimum reliability

# 9-30624

## AirSense Stratos Standalone Command Module

### Technische specificaties

---

#### Algemeen

---

Status indicatie	LED and LCD
Gebruikersinterface	Keypad

---

#### Elektrisch

---

Bedrijfsspanning	21.6 to 26.4 VDC
Stroomverbruik	250 mA

---

#### Uitgang

---

Uitgangshoeveelheid	5 - Pre-Alarm, Alarm, Alarm2, Aux Alarm (n/o) and Fault (n/c)
Type uitgang en classificatie	500 mA @ 30 V

---

#### Fysiek

---

Physical dimensions	427 x 372 x 95 mm (W x H x D)
Netto gewicht	5.2 kg
Colour	Crème
Type montage	Muurmontage
Kabelinvoeren	6 x M20
Material (body)	Polycarbonaat

---

#### Omgeving

---

Operating temperature	-10 to +60°C (EN54-20)
Relative humidity	0 to 90% noncondensing
Omgeving	Binnen
IP rating	IP40

---

#### Mechanical

---

Material	Sheet steel enclosure with plastic front cover
----------	--

---



Als een bedrijf van innovatie behoudt Carrier Fire & Security zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar [be.firesecurityproducts.com](http://be.firesecurityproducts.com) of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 7 March 2024 - 11:01