

# 9-30671-ULF

## AirSense Stratos Micra 25 High Sensitivity Smoke Detector - UL & FM

### Description

---

The Stratos Micra 25 is designed to provide very high sensitivity smoke detection in a small package.

ClassiFire Perceptive Artificial Intelligence ensures that the detector operates at optimum sensitivity for the protected environment, without the need for complex setup. This means the product will configure itself to provide high sensitivity in a computer room or reduced sensitivity in a smoky area.

The detector is designed to fit into a Docking Station. All sampling pipes and cables are connected to the Docking Station as a first fix operation leaving the detector to be fitted during the final commissioning phase if required. This ensures that detectors are less likely to be damaged during the installation.

Upgradable volt-free Fire and Fault relay outputs are available for remote monitoring by local fire detection or BMS systems.

### Typical Applications

---

- Data storage units
- Prison cells
- Plant rooms
- Air conditioning units
- Equipment racks
- Computer rooms
- Air duct protection
- Heritage property protection
- Critical equipment
- Anti-smoking enforcement
- Motor rooms

### Options Available

---

- Addressable Protocol Interface Cards APIC™ available
- Command Module available for central monitoring and display
- SenseNet compatible - up to 127 detectors per loop
- Remote Display units available
- Suitable for MatrixScan, a patented software system which provides virtual addressable location detection - e.g. 10 physical detectors would provide up to 45 unique addressable locations.



### Details

---

- Ultra small low cost aspirating smoke detector for easy and discreet installation
- High sensitivity provided by laser based forward light scatter for reliable early warning
- Unique ClassiFire® Perceptive Artificial Intelligence system that dynamically adjusts the detector's operating parameters, allowing for day to day changes in the protected environment and dust separation system contamination
- Unwanted alarms from dust are avoided using patented Dual Technology LDD 3D3 Laser Dust Discrimination and elimination system
- RS485 communications built in as standard for networking and remote communications
- UL listed and FM approved

# 9-30671-ULF

## AirSense Stratos Micra 25 High Sensitivity Smoke Detector - UL & FM

### Technische specificaties

---

#### Elektrisch

---

Bedrijfsspanning	21.6 to 26.4 VDC
Current consumption	250 mA

---

#### Detectie

---

Detectie principe	Laser light scattering mass detection and particle evaluation
Deeltjes gevoeligheidsbereik	0.003 $\mu$ to 10 $\mu$

---

#### Fysiek

---

Physical dimensions	145 x 220 x 85 mm (W x H x D)
Netto gewicht	1.7 kg
Colour	Crème
Type montage	Muurmontage
Kabelinvoeren	2 x M20
Material (body)	Plaatstalen behuizing

---

#### Omgeving

---

Operating temperature	-10 to +60°C (EN54-20)
Relatieve vochtigheid	0 to 90% noncondensing
Omgeving	Binnen
IP rating	IP40

---

#### Regelgeving

---

Certificering	FM, UL
---------------	--------

---

#### Detection

---

Measurement range (%Obs/m)	0.0015% to 25%
Alarm levels	4 (Aux, Pre-alarm, Alarm and Alarm 2)

---

#### Sampling pipework

---

Inlets	1
Diameter	27mm OD
Exhaust	1 (optional)

---

#### Outputs

---

Standard	2 - Alarm (n/o) and Fault (n/c)
Rating	500mA @ 30V
Expansion	Optional input and relay card

---

#### User interface

---

Indicators	LED
------------	-----

---

#### Networking

---

SenseNET (RS-485)	On-board
-------------------	----------

---



Als een bedrijf van innovatie behoudt Carrier Fire & Security zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar [be.firesecurityproducts.com](http://be.firesecurityproducts.com) of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 15 February 2024 - 9:03