

## FE560

**Kleefmagneet voor vloer/wandmontage. Universeel instelbaar. 'Max. lengte 200 mm. Voorzien van onderbreekknop.**

### General

---

The FE560 is a VdS approved door holder with a universal adjustable tube with a reach of between 156.5 and 175 mm when used in 180° configuration and between 125 and 150 mm used in 90° configuration. It is normally very well suited for applications where the height of the magnet may need adjustment to suit the conditions. It may be used in floor, ceiling or wall mount applications, and is supplied with a manual release button.

### A magnet for all occasions

---

The FE500 series door holding magnets are the result of years of specialised development. Rated at just 1.5 W @ 24VDC, these powerful magnets pack a holding power of 490 N. The FE560 has a spring-loaded pin to ensure ejection against remnant magnetism.

### Application friendly

---

The FE500 series offer cost effective solutions without sacrificing performance. Reinforced aluminium gives it a smart look and rugged endurance, whilst reinforced wall mount aluminium extensions allow up 175 mm distance from the wall. Keeper plates are not supplied with the magnet and can be ordered separately according to the application.

### Installer friendly

---

For practical ease of installation, all units are complete with electrical terminations. Protection diodes prevent electromagnetic pulses and reverse polarity protection, and speeds up installation. The mountings are predrilled in a practical, standard format for rapid mounting.

### Approvals

---

All models are VdS approved.



### Details

---

- Wall, floor or ceiling mount
- Low power - 1.5 W
- 490 N holding power on VDS coils
- 100% duty cycle
- Anti-remnant ejector
- Protection diode and reverse polarity protection
- Release button
- VdS Approved (see specification)

# FE560

Kleefmagneet voor vloer/wandmontage. Universeel instelbaar. 'Max. lengte 200 mm. Voorzien van onderbreekknop.

## Technische specificaties

---

### Algemeen

---

|   |             |
|---|-------------|
| Houdkracht N (Newton)                     | 490         |
| vrijgaveknop                              | Ja          |
| Beveiliging tegen polariteitsverwisseling | Yes (diode) |

---

### Elektrisch

---

|                   |         |
|-------------------|---------|
| Type voeding      | 24 VDC  |
| Vermogensverbruik | 1.5 W   |
| Stroomverbruik    | 62.5 mA |

---

### Fysiek

---

|                    |   |
|--------------------|---|
| Fysieke afmetingen | 125 to 150 x 92.5 mm (mounting @ 90° H x W)<br>156.5 to 175 x 70 mm (mounting @ 180° L x Ø) |
| Kabelinvoeren      | -   |

---

### Omgeving

---

|                  |      |
|------------------|------|
| IP-classificatie | IP42 |
|------------------|------|

---

### Regelgeving

---

|               |     |
|---------------|-----|
| Certificering | VdS |
|---------------|-----|

---

### Compatibele producten

---

| Categorie   | Referentie | Beschrijving                                     |
|-------------|------------|--|
| Deurhouders | FE527      | Standaard ankerplaat, niet verstelbaar.          |
| Deurhouders | FE529      | Ankerplaat met verstelbare voorplaat, max. 120°. |

---



Als een bedrijf van innovatie behoudt Carrier Fire & Security zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar [be.firesecurityproducts.com](https://be.firesecurityproducts.com) of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 3 April 2024 - 16:56