GS300

Piezo glassbreak detector 2 m

High Performance

The glassbreak detector GS300 is designed to detect the specific ultrasonic frequency range produced by breaking glass. Knocks and other normal disturbances to a windowpane do not trigger an alarm. Suitable for use on standard window glass or plate glass the GS300 provide a 2 meter radius of protection. The detector may be fitted as close as 2 cm from the window frame and still provide a full 2 metre radius of coverage on standard glass. The detector is moulded into a plastic housing and delivered with 2m cable as a standard (exists also in 6 & 20 meters). They are featuring a built-in latch LED indicator for easy location of alarmed detectors.



Details

- Small and unobtrusive
- Latching alarm indication
- 2m radius protection
- Easy to install
- No adjustment
- Tamper proof

GS300
Piezo glassbreak detector 2 m

Technische specificaties

Algemeen

Technologie	Piezo
Glassoorten	Vlak
Bereik	2 m radius
Sabotageschakelaar	Nee

Bedraad / draadloos

Bedraad / draadloos	Bekabeld

Elektrisch

Waarde voeding	3 to 16 VDC
Stroomverbruik	9 mA at 12 VDC 4 mA at 6 VDC

Fysiek

Fysieke afmetingen	37 × 19 × 12 mm
Netto gewicht	50 g
Kleur	Wit
Type montage	Oppervlaktemontage

Omgeving

Bedrijfstemperatuur	-25 to +70°C
IP-classificatie	IP67

Regelgeving

Certificering	EN50131 Grade 2, VdS

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 18 June 2026 - 14:24