IM1640PSG

Surface mount contact, supervised cable, NFA2P

Commercial surface mount contact

The IM1640 series commercial surface mount contacts are specifically designed to work on metal frames. The contacts can be used in harsh environments. Special version with armoured cable and including junction box is available.



Details

- Designed for use in harsh environments
- Magnet specifically designed to work on metal frames
- Tamper loop
- Version with armoured cable

IM1640PSG

Surface mount contact, supervised cable, NFA2P

Technische specificaties

Algemeen

Type toepassing	Oppervlaktemontage
Type contact	NC
Aansluiting	4 wires, 85 cm

Bedraad / draadloos

Bedraad / draadloos	Bekabeld
Werkingsafstand	25 mm

Elektrisch

Spanning	max. 48 VDC

Fysiek

Fysieke afmetingen	72 x 23 x 19 mm (W x H x D)
Afmetingen magneet	23 x 72 mm
Afmetingen contact / sensor	23 x 72 mm
Kleur	Wit

Omgeving

Bedrijfstemperatuur	-10 to +55°C

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 13 August 2026 - 11:05