TVF-1105

TruVision 360 Degree IP Dome, 3.0 MPX, PAL, WDR, Indoor,1.19mm fisheye lens, true D/N, 10m IR, 2 way audio (built-in mic & speaker), SD/SHDC slot, PoE (803.af) /12VDC, white

Overview

Ideally suited for a variety of applications including retail, commercial, law enforcement and education environments, the TruVision 360º network dome camera provides high-quality image capture, that delivers a complete view of indoor or outdoor areas for exceptional security coverage. Supporting 3MPx sensors, these cameras are PoE 802.3af powered making installation as easy as running a Category 5e cable to the camera location. Particularly effective in areas where a wide area needs to be covered, such as intersecting corridors, parking garages, counters and warehouses. The 360º camera can also be used in a wall-mount configuration to capture panoramic scenes. With an IR range of up to 10m, they can also be used in low-light environments and for 24/7 exterior surveillance. Extra mounting accessories are available for pendant mount and wall mount installation. The cameras can be used with our TruVision NVRs and Prism

Details

- 3MPx 1/3" progressive scan CMOS
- Up to 2048 x 1536 real-time streaming
- 360° view angle
- Multiple viewing modes
- Multiple ePTZ streams with preset and patrol functions
- Up to 10m IR range
- 2-way audio, built-in mic and speaker
- Built-in SD/SDHC card slot
- Ceiling, wall and desk mount options
- Indoor version
- Operating temperature range -30 to 60°C

TVF-1105

TruVision 360 Degree IP Dome, 3.0 MPX, PAL, WDR, Indoor,1.19mm fisheye lens, true D/N, 10m IR, 2 way audio (built-in mic & speaker), SD/SHDC slot, PoE (803.af) /12VDC, white

Technische specificaties

Algemeen

Technologie	IP
Videostandaard	PAL

Camera

Sensorgrootte	1/3"
Max. resolutie	3 MP
Sensor scan	Progressive
Type sensor	CMOS
Totaal aantal pixels (H x V)	2048 x 1536
Digitale signaal-ruisverhouding	50 dB
Sluitertijd	1/25 to 1/100.000s

Verlichtingsprestaties

WDR	120 dB
Digitale ruisonderdrukking	3D DNR
Dag / nacht	True Day/Night
Gemotoriseerd IR-cutfilter	Ja
Kleurgevoeligheid	0.28lux @(F2.0, AGC ON)
Zwart-wit gevoeligheid	0 lux with IR
Infrarood (IR)	Ja
IR-bereik	10 m
IR-golflengte	850 nm

Encodering

Mainstream compressie	H.264
Max. resolutie @ fps	2048 x 1536 @25 fps
Ondersteuning voor hoge framemodus	50Hz: 1 x fisheye (2048 x 1536, 25fps) or (1536 x 1536, 25fps) or 4 x PTZ (800 x 600, 25fps)

Objectief

Type objectief	Lens omzetten
Brandpuntsafstand	1.19 mm
f-stop	1.4

Netwerk

Integratie	CGI, ONVIF, PSIA

Audio

Audiocompressie	G.711, G.726
Audio-in	Internal Microphone
Audio-uit	Internal Speaker

Opslag

Ondersteuning voor lokale opslag	Ja
Type lokale opslag	Built-in SD/SDHC Slot
Max. SD card capacity	64 GB

Video-intelligentie

Alarmtrigger	Motion detection, Video tampering

Elektrisch

Bedrijfsspanning	12 VDC
Type voeding	PoE in
Vermogensverbruik	12 W max.
Stroomverbruik	1 A

Fysiek

Fysieke afmetingen	167 x 45 mm
Netto gewicht	767 g
Kleur	Wit
Form Factor	360 graden

Omgeving

Omgeving	Binnen
Bedrijfstemperatuur	-30 to +60°C -22 to +140°F

Regelgeving

Conformiteit	C-tick, CE, FCC, REACH, RoHS, UL, WEEE

Als een bedrijf van innovatie behoudt Carrier Fire & Security zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 5 May 2023 - 9:37