

# TVN-2216-2T

TruVision™ NVR 22 recorder, 16 IP channels, 2TB, H.265 NVR, 1.5U



# TVN-2216-2T

TruVision™ NVR 22 recorder, 16 IP channels, 2TB, H.265 NVR, 1.5U

## Technische specificaties

### Algemeen

Technology	IP
Rack mountable	Ja
Rack stacking size	1.5 U
Removable fan	Nee
Redundant power supply	Nee

### Video / audio input

Camera channels	16
Supported video compression standards	H.264, H.265, MPEG-4
Supported video streaming standards	Onvif, PSIA, RTSP, RTSP Custom Protocols

### Local viewing

HDMI output	1
HDMI version	2.0
VGA output	1
BNC output	1
Max. local output resolution	4K

### Weergave op afstand

Software compatibility	Advisor Management Software (ATS8600), TruVision Navigator, TVRmobile, Web Browser
Browser compatibility	Google Chrome, Internet Explorer, Mozilla Firefox, Safari

### Opslag

Storage capacity	2 TB
Maximum recording resolution	12 MP
Recording modes	Alarm, Event, Manual, Time-lapse high, Time-lapse low
External storage	eSATA, NAS, SAN
Hard drive redundancy	Ja
Hard drive grouping	Ja
SAS extension	Nee
Flip-open front panel	Ja
Auto archiving	Ja
Hot spare recorder	Ja
Edge failover recording	Ja

### Netwerken

NIC type	RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
NIC-modus	Network Redundancy
DNS support	DDNS, ezDDNS, Geen IP
HTTPS support	Ja

### Externe interfaces

USB interface back	1
USB interface front	2
Serial interface	RS-232
Alarm inputs	16
Alarm outputs	4
Max. analog audio outputs	1

### Elektrisch

Power supply type	100 tot 240 VAC
-------------------	-----------------

### Fysiek

Colour	Zwart
--------	-------

### Regelgeving

Compliance	CE, REACH, RoHS, UL
------------	---------------------



Als een bedrijf van innovatie behoudt Carrier Fire & Security zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar [be.firesecurityproducts.com](http://be.firesecurityproducts.com) of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 18 April 2024 - 16:50