5815NT-ART

Shatter Pro glasbreukmelder, 360° bereik, straal 0.9-7.6m. Kleur wit

The 5815NT-ART series ShatterPro3 is an advanced series of acoustic glassbreak sensors. In laboratory tests to compare reliability with the excellent proven standard of the ShatterPro2 (GS903N), the ShatterPro3 provides 250 percent better false alarm immunity. The coverage pattern can be easily adjusted to fit small or large rooms. Interference ouside the range will not cause false alarms.

Using the patented "Pattern Recognition Technology", the sensor looks for patterns that are typical for breaking glass. This results into a greater false alarm immunity for the ShatterPro3 range.

Available with a round or rectangular housing, ShatterPro3 can be tested without opening the sensor by using the hand-held glassbreak tester. A simple handclap feature allows end-users to confirm at any time that the ShatterPro3 is operational.



Details

- New "EZ" design for quick and easy installation
- Pattern Recognition Technology for superior detection and false alarm immunity
- Suitable for quiet occupied areas on a perimeter loop
- Automatic test and user verification

5815NT-ART

Shatter Pro glasbreukmelder, 360° bereik, straal 0.9-7.6m. Kleur wit

Technische specificaties

Algemeen

Technologie	Acoustic
Glassoorten	Gelaagd, Vlak, Getemperd, Bekabeld
Bereik	7.5 m radius
Relaisuitgang	CO, open 4 sec on alarm
Sabotageschakelaar	Ja

Bedraad / draadloos

Bedraad / draadloos	Bekabeld

Elektrisch

Waarde voeding	9.5 to 16 VDC
Stroomverbruik	15 mA typical - 25 mA max

Fysiek

Fysieke afmetingen	115 x 70 x 21 mm (L x W x H)
Kleur	Wit
Type montage	Oppervlaktemontage

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 8 June 2026 - 16:31