AB303

Flitslicht, 115 mA, rood

The range of low and high profile XENON beacons offers maximum light output and high efficiency for use in 10-15 V intruder alarms. Tested for IP65 rating, with polycarbonate lenses as standard, they are suitable for the most demanding applications.



Details

- Maximum light output
- High efficiency
- Tested to IP65 rating
- Polycarbonate lens

AB303
Flitslicht, 115 mA, rood

Technische specificaties

Algemeen

Accessoire groep	Flits
Type	Accessoire

Flash-specificaties

Lichtopbrengst	0.9 nominal J
Flitsfrequentie	60 flashes/minute

Elektrisch

Vermogensverbruik	1 W
Bedrijfsspanning	12 V
Stroomverbruik	115 mA

Fysiek

Fysieke afmetingen	75 x 51 mm (Ø x H)
Kleur	Zwart

Omgeving

Bedrijfstemperatuur	-30 to 70°C
IP-classificatie	IP65

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 3 November 2025 - 12:41