AS272

Binnensirene met 2 tonen en noodstroomaansluiting. Exclusief accu BS170N

The AS270 series of sirens is ideal for use as an internal alarm sounder for residential and industrial alarm applications.



Details

- Low current consumption
- 2 tones
- Pry-off & opening tamper protection
- Easy to install (1 fixing screw for cover)
- Vertical or horizontal mounting
- Self activating version available
- ANPI, NFA2P and VdS version available

AS272

Binnensirene met 2 tonen en noodstroomaansluiting. Exclusief accu BS170N

Technische specificaties

Algemeen

Accessoire groep	Sirene
Type	Binnensirene
Sirene uitgang (dB @ afstand)	101 dB at 1 m (typical)

Elektrisch

Waarde voeding	10.0 to 14.2 VDC
Bedrijfsspanning	10 to 14.2 V
Stroomverbruik	120 mA at 12 VDC (typical)
Accucapaciteit	280 mAh, 10.8 V NiCd

Fysiek

Fysieke afmetingen	155 x 114 x 44 mm
Netto gewicht	220 g
Kleur	Wit
Materiaal	ABS

Omgeving

Bedrijfstemperatuur	-25 to +55°C
IP-classificatie	IP30

Regelgeving

Certificering	CE

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 16 June 2026 - 15:32