AS610

Buitensirene in polycarbonaat behuizing, kleur wit, oranje flitslicht

Application

The AS600 series is a range of high quality installer-friendly sirens with a sound output of 120 dB @ 1 m, that meets today's security and environmental requirements. The sirens are housed in attractive covers made from UV-proof and impact resistant 3.5 mm polycarbonate. They have a foam-resistant steel inner cover for the ultimate protection and offer a choice of strobe colours.



Details

- Attractively shaped housings
- High-quality dual skinned design
- 120 dB @ 1 m sound output
- Lead acid battery back-up for up to 7.2 Ah
- Steel inner cover with foam resistant grid
- Fully potted electronics
- Pry-off and opening tamper detection
- Strobe flash light
- Self detection of cable cutting or tampering
- Automatic polarity selection
- Independent hold-off for both : beacon & siren
- Choice of cut-off time

AS610

Buitensirene in polycarbonaat behuizing, kleur wit, oranje flitslicht

Technische specificaties

Algemeen

Accessoire groep	Sirene
Type	Buitensirene
Sirene uitgang (dB @ afstand)	120 dB at 1 m (typical)

Flash-specificaties

Lichtopbrengst	100,000 peak lumens
Flitsfrequentie	60 flashes/minute

Elektrisch

Bedrijfsspanning	13 to 14.2 V
Stroomverbruik	600 mA 25 mA (standby current) 110 mA (operating current)

Fysiek

Fysieke afmetingen	210 x 300 x 87 mm (W x H x D)
Netto gewicht	2669 g
Materiaal	Polycarbonaat

Omgeving

Bedrijfstemperatuur	-25 to 55 °C
IP-classificatie	35

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 23 June 2026 - 11:47