



ATS1236

32 zones 433Mhz wireless receiver DGP

Increasing zone capacity

The ATS1236 wireless receiver adds wireless capabilities to the Advisor Advanced range of panels.

The wireless DGP supports most of the legacy 433 MHz 63-bit transmitters as well as the new generation of 433 MHz LoNa transmitters of which the wireless communication is fully encrypted, avoiding unauthorized interference. Up to 32 wireless sensors and up to 16 keyfobs can be learned in.

The ATS1236 wireless receiver provides two wired zone inputs and one programmable relay output.

Installation and programming

The wireless DGP needs to be installed outside the panel housing in order to assure a maximum wireless range. The 433MHz wireless solution will monitor the status and presence of each wireless device and will respond in case of an RF jamming condition.

The ATS1236 wireless receiver can be programmed from the keypad as well as from the downloader. The firmware of the module is remotely upgradeable.



Details

- Adds wireless capabilities to Advisor Advanced
- Two wired zone inputs
- One programmable SPDT Form C relay output
- Supports legacy 63-bit 433 MHz and new LoNa 433 MHz transmitters
- Learn-mode technology
- Removable terminals
- EN50131-1/EN50131-3/EN50131-6 Grade 2 Class II (pending) INCERT (pending)
- Firmware upgradeable

ATS1236

32 zones 433Mhz wireless receiver DGP

Technische specificaties

Algemeen

Expander type	Draadloze uitbreiding
Product line	Advisor Advanced
Connection type	Databus connection
Compatibiliteit	Advisor Advanced MR 4.2 or higher

Systeem

Adressering	DIP Switches
-------------	--------------

Ingangen

Total	32
Aantal draadloze zones	32 wireless sensors + 16 keyfobs
Onboard	2 wired

Uitgangen

Onboard	1
Type of outputs	SPDT Form C relay

Draadloos

Bedrijfsfrequentie	433 MHz legacy, 433 MHz LoNa
--------------------	------------------------------

Elektrisch

Operating voltage	12Vdc via bus
Current consumption	typical : 47 mA maximum : 51 mA
Geïntegreerde voeding	Nee

Fysiek

Physical dimensions	155 x 95 x 26 mm
Net weight	0.160 kg
Colour	Wit
Material	ABS plastic

Omgeving

Operating temperature	-10°C to 55°C
Relative humidity	90% relative humidity non-condensing
Environment	EN50130-5 ; Klasse II - Binnen (algemeen)

Regelgeving

Compliance	CE
Certification	CE, EN50131 Grade 2, INCERT
Standaarden	EN50131 Grade 2 & INCERT pending



Als een bedrijf van innovatie behoudt Carrier Fire & Security zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 26 September 2023 - 16:56