ATS1475X10

10x10Pack ATS1475 ATS kwaliteit Hitag

Product Overview

These cards are to be used on ATS readers. The cards are unprogrammed and have the number printed for easier administration. Both the smart ship and antenna are embedded inside the card. Printing is possible on the card using any industry standard printer and because each card has superior finished surface you will always have excellent printing results.



Details

- Read/Write capability
- Ability to program a unique 4-billion, 4-byte security code
- 4 memory areas for credit applications
- Packed by 10

ATS1475X10

10x10Pack ATS1475 ATS kwaliteit Hitag

Technische specificaties

Systeem

Leesafstand	0 to 60 cm
Aangepast datamodel	Nee
Ondersteunde lezers	ATS Proximity Readers

Technologie

Type kaart	Nabijheid
Bedrijfsfrequentie kaart	125 KHz
Ondersteunde technologie 125 kHz	HiTag 2

Printen

Direct oppervlakte printen	Ja

Bestelinformatie

Minimum bestelhoeveelheid	1
Kaarten / tags in verpakking	100

Fysiek

Materiaal	PVC
Vormfactor	CR80 (Credit)
Fysieke afmetingen	86 x 54 mm
Kleur	Wit

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 18 June 2026 - 14:24