BS121N

Droge accu, 12 V, 1.2 Ah, VdS

Product overview

Sealed lead acid battery 12 V, 1.2 Ah with Fast-on 4.8 mm terminal type.



Details

- Maintenance free 12 VDC
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechangeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS121N

Droge accu, 12 V, 1.2 Ah, VdS

Technische specificaties

Algemeen

Type product	Batterijpak, NiCd batterij, Verzegelde loodzuurbatterij

Elektrische eigenschappen

Nominale spanning	12 V
Nominale capaciteit	1.2 Ah
Inwendige weerstand (circa)	75 mOhm

Opladen / ontladen

Max. laadspanning	13.8 VDC at +20°C
Max. Laadstroom	0.36 A
Max. Ontlaadstroom	6 A

Fysiek

Fysieke afmetingen	97 x 43 x 53 mm
Netto gewicht	0.596 kg
Verzendgewicht	0.596 kg
Materiaal	Metaal
Type aansluiting	Fast-on 4.8 mm

Omgeving

Brandvertragend	Nee
Bedrijfstemperatuur	0 to +40°C
Opslagtemperatuur	-15 to +50°C

Regelgeving

Conformiteit	CE, RoHS 2, WEEE
Certificering	VdS

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 17 November 2026 - 14:55