BS131N

Droge accu, 12 V, 18 Ah, VdS

Product overview

Sealed Lead Acid battery 12 V / 18 Ah with MS bolt & nuts terminal type.



Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechangeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS131N

Droge accu, 12 V, 18 Ah, VdS

Technische specificaties

Algemeen

Type product	Verzegelde loodzuurbatterij

Elektrische eigenschappen

Nominale spanning	12 V
Nominale capaciteit	18 Ah
Inwendige weerstand (circa)	10 mOhm

Opladen / ontladen

Max. laadspanning	13.8 VDC at +20°C
Max. Laadstroom	5.4 A
Max. Ontlaadstroom	90 A

Temperatuur

Temperatuur bij opladen	0 to +40°C
Temperatuur bij ontladen	-15 to +50°C

Fysiek

Fysieke afmetingen	181 x 76 x 167 mm
Netto gewicht	6.283 kg
Verzendgewicht	6.283 kg
Materiaal	ABS
Type aansluiting	MS bolt & nuts

Omgeving

Brandvertragend	Nee
Bedrijfstemperatuur	+0 to +40°C
Opslagtemperatuur	-15 to +50°C

Regelgeving

Conformiteit	CE, RoHS 2, WEEE
Certificering	VdS

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 17 November 2026 - 14:55