

CDC4

Intelligent 4-8 door / lift controller with 12 V PSU

Product overview

The CDC4 is a 4-8 door & lift controller. It provides for a complete and versatile access control solution to extend the Advisor Advanced and Axon system with advanced access control functions. It provides a fully integrated real time alarm and access control for four up to eight doors or lifts, with power supply and housing. A total of 12 door/lift controllers can be connected to an Advisor Advanced or Axon panel providing for a total of 48 up to 96 full access doors. The CDC4 door/lift controller can operate off-line with no degradation in performances, should communication with the Advisor Advanced panel fail as it offers full offline operation. This combined intrusion and access solution reduces wiring and required devices as the same devices like readers and inputs can be used for both purposes. Door and lift control can be used in one single door controller by configuring doors to lifts.

Expanders

Expanders are used to expand the number of alarm inputs in an Advisor Advanced and Axon system. Expanders allow inputs and outputs/relays to be connected at a location remote from an Advisor Advanced or Axon panel. Expanders communicate via poll & reply messages. Detectors, door contacts and other detection devices are connected to expanders that report any change of state to the control panel for processing. Available expanders include support for conventional devices, wireless devices as well as intelligent addressable devices. A special expander is available providing expansion of four to eight intelligent doors or lifts.

Special features

Besides standard intrusion and access control options, the solution offers special features that are only possible due to the real combination of both. These features vary from changing security on doors when the intrusion area has disarmed, locking doors when the intrusion area arms, preventing access based on the intrusion area status or starting automatic arming when the last user has left an access control region. Special access control features include High Secure users for high secure areas like vaults, support for macro's to complement the standard features.

The lift functionality offers a solution where lift floor buttons can be controlled by access levels of users. Outputs referring to floors for that lift will switch to only allow press the button for the allowed floors.

Security

The CDC4 has been designed with focus on security. Not only providing fully encrypted communication between the controller and management application, but also between the CDC4 controller and the Advisor Advanced panel or Axon panel., between the card and readers as well as between readers and the CDC4 controller or the Advisor Advanced panel or Axon panel. In other words, CDC4 provides communication security from card to software.



Details

- Real time alarm & access control on 4-8 doors / lifts per controller
- Complete database for offline operation
- Up to 12 CDC4 door controllers providing 48 to 96 intelligent doors or lifts
- Compatible with Axon and Advisor Advanced panels
- Any door can be configured as lift: use both together in one controller
- Full access control features: interlocking, user count, high secure users, anti-passback with regions
- Up to 65532 users with card and/or PIN
- Up to 32 readers per CDC4 and 6 per door
- Two local databuses with configurable protocol
- Supporting Secure readers, OSDP readers and wireless locks
- On board inputs, door relays, IP connection and expansion options
- Extended mode operation: access control users managed by Advisor Management
- Anti-passback between all door controllers in standard mode connected to Advisor Advanced

Connectivity

Any CDC4 can operate in two modes. Depending the mode selected the CDC4 is controlled completely through the Advisor Advanced or Axon panel providing four doors or lifts per CDC4 which is named the standard mode. In standard mode the CDC4 acts like legacy door controllers providing the same features and user data for the door controller and the Advisor Advanced or Axon panel.

In extended mode the CDC4 is also configured through the Advisor Advanced panel using the ATS8500 or ATS8550 downloader. Even in extended mode the CDC4 exchanges intrusion information with the Advanced panel. In extended mode however the CDC4 is also directly connected via IP to Advisor management for configuration of access and intrusion users while providing support of up to 8 doors or lifts per CDC4. Advisor Management sends intrusion related user data to the Advisor Advanced panel and access related data directly to the CDC4. Extended mode is not yet supported on Axon control panels.

CDC4

Intelligent 4-8 door / lift controller with 12 V PSU

Technische specificaties

Algemeen

Type uitbreiding	Deurcontroller
Productlijn	Advisor Advanced
Type aansluiting	RS485 (to Advisor Advanced), IP (to Advisor Management)
Compatibiliteit	Advisor Advanced (not Advisor Master), Axon
Max. afstand van paneel	1.5 km using advised cable
Max. per paneel	Up to 12, depending on intrusion panel
Gespecificeerde kabel	WCAT52 / WCAT54 or equivalent

Systeem

Users	Up to 65532
PIN codes	All
Door groups	128 to 50,000
Timezones / holidays	24 to 1000
Adressering	DIP Switches
End-of-line weerstand	Selectable

Ingangen

Totaal	32 for intrusion use
Onboard	8
Uitbreidbaar	24 for intrusion use

Uitgangen

Totaal	16 for intrusion use
Onboard	4
Uitbreidbaar	8
Type uitgangen	Relays/Open Collector
Relais	4
Maximaal aantal uitgangen	128
Sirene uitgangen	1

Back-up

Type batterij	Up to 26 Ah Max 18 Ah in housing
Dynamisch accutest	Supported

Elektrisch

Type voeding	230 VAC
Waarde voeding	230 VAC +10%, -15%, 50 Hz
Vermogensverbruik	3A at 13.8 VDC
Stroomverbruik	251 mA (incl Ethernet)
Geïntegreerde voeding	Yes

Fysiek

Fysieke afmetingen	409 x 593 x 112 mm
Colour	Beige
Materiaal	Staal (geverfd)
Behuizing	Metal

Omgeving

Bedrijfstemperatuur	0 to +50°C
Storage temperature	-20 to +80°C
Relatieve vochtigheid	93% noncondensing
Omgeving	Binnen
IP-classificatie	IP31

Regelgeving

Conformiteit	CE
Certificering	CE