# DC127


**Inbouwcontact, zelfborgend, sabotagelus, 2m, wit, afstand ±31mm, NC.**

## Press-Fit Contact

The DC121 press fit switch is an 11 mm diameter magnetic contact with wire leads. Use no glue or screws to mount; small ribs on the housing hold the contact in place. Heavy-duty housing resist crushing from swelling wood. An extra wide gap version, DC127, is available for applications that may be prone to false alarms caused by loose fitting doors. The DC222 is a variant with a change-over contact type.

## Applications

For recessed applications, either indoor or outdoor. Also useful in protecting china cabinets or closets, double-hung windows and aluminium windows.



## Details

- 11 mm press-fit mounting; no screws or glue needed
- Attractive, added security of recessed installation
- Heavy-duty housing resists crushing
- Available in different cable lengths
- Tamper loop provided

# DC127

## Inbouwcontact, zelfborgend, sabotagelus, 2m, wit, afstand ±31mm, NC.

## Technische specificaties

### Algemeen


| | |
|---|---|
| Type toepassing | Verzonken montage |
| Type contact | NC |
| Aansluiting | 4 wires, 2 m |

### Bedraad / draadloos

| | |
|---|---|
| Bedraad / draadloos | Bekabeld |
| Werkingsafstand | 31 mm (max.) |

### Fysiek

| | |
|---|---|
| Fysieke afmetingen | 11 x 33 mm (Ø x L) |
| Kleur | Wit |




Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 13 August 2026 - 11:05