DC142

Industr. opbouwcontact, schroefaansluiting, wit, schakelafstand ± 75mm, NC.

Industrial Surface Mount Contact

The DC116 series features a wider make distance and works better on steel without time-consuming installation of brackets. A wider break distance helps prevent false alarms caused by loose fitting doors.

Applications

The contacts are used to protect openings such as metal entry/exit doors, overhead doors, roof hatches or hinged skylights.



Details

- Rugged design for industrial applications
- Models for use on steel without time-consuming brackets
- Concealed terminals resist tampering and inadvertent shorting
- Easy clamping terminals speed installation
- Mounting screws included

DC142

Industr. opbouwcontact, schroefaansluiting, wit, schakelafstand ± 75mm, NC.

Technische specificaties

Algemeen

Type toepassing	Oppervlaktemontage
Type contact	NC
Aansluiting	Screw

Bedraad / draadloos

Bedraad / draadloos	Bekabeld
Werkingsafstand	75 mm (max.)

Fysiek

Fysieke afmetingen	99 x 17 x 15 mm
Kleur	Beige



Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 13 August 2026 - 11:05