

# TVK-600

## TruVision RS485/IP keypad, 4-axis joystick, 12VDC

### Overview

The TVK-600 keypad has been designed to be used with the line of TruVision NVRs, DVRs, PTZ cameras, encoders and decoders. A TVK-600 lets you easily control the monitor outputs of a recorder and a decoder, allows precise PTZ control, and gives you full control of every recorder's user interface using only the keypad.

### Full featured

The TVK-600 contains all features to control a TruVision device efficiently.

The keypad can communicate via IP or RS485 with supported recorders and cameras.

The configuration of the keypad is done via a web browser.

Different user modes can be selected via the on-screen menu of the LCD display.

The keypad supports up to 1000 devices via keyboard mode.

Users can navigate through the menu of a recorder and control PTZ cameras via the 4-axis joystick.

### Why TVK-600?

The TVK-600 lets you control your video system via one user interface without using a PC.

### Applications

The TVK-600 is ideal for guard rooms and monitoring centers.



### Details

- Control a variety of NVRs, DVRs, decoders, PTZ cameras with one keypad
- Communication via IP or RS485
- 4-axis joystick
- Numeric and functional buttons
- Supports PTZ control (analog and IP)
- Control monitor outputs of recorders
- Supports up to 1000 devices via keyboard mode
- Configuration and device management via webpage
- Control the recorder OSD
- Set and call presets and preset tours of PTZ cameras

# TVK-600

TruVision RS485/IP keypad, 4-axis joystick, 12VDC

## Technische specificaties

### Algemeen

Type toetsenbord / controller	Analoog / Serieel, IP
-------------------------------	-----------------------

### Bediening

Type joystick	4-assig
Toetsen	Numeric and functional

### Gebruikersinterface

Weergavetype	128x64 pixel screen
--------------	---------------------

### Interfaces

Interface aansluiting	Ethernet, RS-485
Network interface	10 / 100 Mbps self-adaptive Ethernet interface
USB	USB 2.0

### Elektrisch

Type voeding	12 VDC
Waarde voeding	12 V
Vermogensverbruik	<= 4.5 W

### Fysiek

Fysieke afmetingen	435 x 193 x 110 mm
Netto gewicht	1 kg
Kleur	Zwart

### Omgeving

Bedrijfstemperatuur	-10 to +55°C
Relatieve vochtigheid	10 to 90%

### Regelgeving

Conformiteit	CE, RoHS, WEEE
--------------	----------------

### Supported products

#### Devices

TruVision PTZ cameras:  
TruVision S1 PTZ cameras (TVP-310x / 110x / 3122 / 1122)  
TruVision IP Compact PTZ cameras  
TruVision IP Full Size PTZ cameras  
TruVision Stainless Steel IP PTZ cameras  
TruVision TVI PTZ cameras

#### TruVision recorders:

TVN 11 series  
TVN 21 series  
TVN 22 series  
TVR 15HD series  
TVR 45HD series  
TVR 46 series  
TVR 40 series  
TVR 41 series  
TVR 42 series  
TVR 60 series

#### TruVision decoders:

TVE-DEC11

TVE-DEC12

TruVision encoders and non-PTZ IP cameras:  
only as input.

See configuration manual (Appendix A) for more detailed information.



Als een bedrijf van innovatie behoudt Carrier Fire & Security zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar [nl.firesecurityproducts.com](http://nl.firesecurityproducts.com) of neem contact op met uw verkoopvertegenwoordiger.