

TVN-2216-2T

TruVision NVR 22, H.264/265, 16 kanalen IP, 2TB



TVN-2216-2T

TruVision NVR 22, H.264/265, 16 kanalen IP, 2TB

Technische specificaties

Algemeen

Technology	IP
Rack mountable	Ja
Rack stacking size	1.5 U
Removable fan	Nee
Redundant power supply	Nee

Video / audio input

Camera channels	16
Supported video compression standards	H.264, H.265, MPEG-4
Supported video streaming standards	Onvif, PSIA, RTSP, RTSP Custom Protocols

Local viewing

HDMI output	1
HDMI version	2.0
VGA output	1
BNC output	1
Max. local output resolution	4K

Weergave op afstand

Software compatibility	Advisor Management Software (ATS8600), TruVision Navigator, TVRmobile, Web Browser
Browser compatibility	Google Chrome, Internet Explorer, Mozilla Firefox, Safari

Opslag

Storage capacity	2 TB
Maximum recording resolution	12 MP
Recording modes	Alarm, Event, Manual, Time-lapse high, Time-lapse low
External storage	eSATA, NAS, SAN
Hard drive redundancy	Ja
Hard drive grouping	Ja
SAS extension	Nee
Flip-open front panel	Ja
Auto archiving	Ja
Hot spare recorder	Ja
Edge failover recording	Ja

Netwerken

NIC type	RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
NIC-modus	Network Redundancy
DNS support	DDNS, ezDDNS, Geen IP
HTTPS support	Ja

Externe interfaces

USB interface back	1
USB interface front	2
Serial interface	RS-232
Alarm inputs	16
Alarm outputs	4
Max. analog audio outputs	1

Elektrisch

Power supply type	100 tot 240 VAC
-------------------	-----------------

Fysiek

Colour	Zwart
--------	-------

Regelgeving

Compliance	CE, REACH, RoHS, UL
------------	---------------------



Als een bedrijf van innovatie behoudt Carrier Fire & Security zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 18 April 2024 - 16:50