VE1012PI

PIR met V2E, 12 m bereik, 9 velden. EN grade 2, huisdierbestendig tot 35 cm

The power of mirror

Our motion sensors have the most advanced and sophisticated optics in the security industry. This unique optical mirror technology is a step and gliding focus, which creates a continuous curtain resulting in a sensor that never loses track of the object.
To increase detection coverage, the 1000 series sensors use the 3Brid orthogonal curtain design. This is a horizontal mirror structure that produces curtains with vertical orientation to detect infrared. This orthogonal invention is the key in adding curtains to the mirror without sacrificing signal strength, nor increasing the size of the sensor.

Patented Vector pyro

Infrared signals are captured by the pyro-electric sensor that is placed in the detectors' focal point. The conventional pyro generates a one-dimensional signal (value) to detect the presence of a source, and therefore its detection probability within the area is entirely determined by the resolution of the optics of the motion detector.

Due to the unique construction of the patented Vector pyro, a thermal source will generate a multi-dimensional signal (vector), allowing the pyro to determine not only the presence but also the direction of motion of a thermal source. This now means that the detection probability is equal to the product of the resolution of the optics and the multi-dimensional output of the pyro. This is a major advance in PIR technology capability.

V2E signal processing

The VE series of motion detectors incorporate a patented Vector Verified Enhanced (V2E) signal processing. Each type of signal source will generate a unique vector output captured by the Vector pyro. The digital signal processing will analyze each vector's shape and pattern, allowing it to distinguish different signal sources. It means that VE series motion sensors will not only identify non-thermal signal sources, but also filter out any potential nuisance signals such as stationary thermal sources, ventilators or strong light sources, and react only to alarm signals from intruders. Our PIR motion sensor with vector pattern recognition is unique.

Easy to install

PIRs of the 1000 series are the most rewarding sensors to install:
1. Tolerate wall angle deviation and different mounting heights.
2. Limited loss of coverage when objects are placed in the field of vision.
3. No range setting is required thanks to constant range sensitivity.
4. Plug-in electronics.

Complete family

The 1000 series are part of our range of motion sensors. This family includes motion sensors with variants in housing size, detection range, anti-masking, dual detection technology, addressable interfacing,



Details

- Passive Infra Red motion sensor
- 3-Brid Gliding Focus Curtain mirror
- Plug-in electronics
- Sealed optics
- "V2E" signal processing for false alarm immunity
- 15Kg pet tolerance
- Under crawl detection
- Selectable coverage pattern using mirror masks
- Auto focus with constant range sensitivity
- No adjustment required for different mounting heights
- Tolerates wall angle deviation
- EN50131-2-2 Grade 2 certified
- Several European approvals

wireless transmission and more. This range covers all applications where security needs to be safeguarded.
The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.

VE1012PI

PIR met V2E, 12 m bereik, 9 velden. EN grade 2, huisdierbestendig tot 35 cm

Technische specificaties

Algemeen

Technologie	PIR
Type toepassing	Muurmontage
Anti-maskering	Nee
Ongevoelig voor huisdieren	Ja
Camera	Nee
Signaalverwerking	Vector Verified Enhanced (VE2)
Afneembeveiligingskit	ST400 (optional)
Opstarttijd detector	25 s

Detectie

Max. detectiebereik	12 m
Detection range	12 m 40 ft
Aantal gordijnvelden	9
Openingshoek (kijkveld)	86°
Onderkruipbeveiliging	Ja
Doel snelheidsbereik	0,3 to 3.0 m/s
Alarmgeheugen	Nee
Alarmtijd	3 s
Piek-tot-piek rimpelbestendigheid	2V (at 12 VDC)

Bedraad / draadloos

Bedraad / draadloos	Bekabeld

Ingangen / uitgangen

Alarmrelais karakteristiek	NC, 80 mA 30 VDC, Form A
sabotagerelais karakteristiek	NC, 80 mA 30 VDC, Form A
Relais configuratie	Isolated or 4k7 EOL
Stuurdraden op afstand	Walk test

Elektrisch

Bedrijfsspanning	9 to 15 VDC
Stroomverbruik	5.5 mA

Fysiek

Fysieke afmetingen	108 x 60 x 46 mm (W x H x D)
Netto gewicht	120 g
Kleur	Wit
Montagehoogte	2.3 to 3 m

Omgeving

Bedrijfstemperatuur	-10 to +55°C 14 to 130°F
Relatieve vochtigheid	95 % relative humidity
Omgeving	Binnen
IP-classificatie	IP30

Regelgeving

EN50131 Grade	Grade 2



Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 18 June 2026 - 14:33