9-30709

AirSense Stratos Standalone Command Module

Description

AirSense Stratos Command Module provides a single location display, control and interfacing option for systems of upto 127 detectors. Command Module allows global programming of all detector functions simultaneously.

The integral bargraph automatically displays the status of the detector with the highest alarm level to identify potential problem areas.

The PIN protected programmer enables global entry of all detector settings to significantly reduce commissioning time.

Typical Applications

- Data storage units
- Prison cells
- Plant rooms
- Air conditioning units
- Equipment racks
- Computer rooms
- Air duct protection
- Heritage property protection
- Critical equipment
- Anti-smoking enforcement
- Motor rooms

Options Available

- Addressable Protocol Interface Cards APIC™ available
- SenseNet compatible - up to 127 detectors per loop
- Remote Display units available
- Suitable for MatrixScan, a patented software system which provides virtual addressable location detection - e.g. 10 physical detectors would provide up to 45 unique addressable locations.

Szczegóły

- RS485 communications built in as standard for networking and remote communications
- Network control of 127 detectors
- Built in Short Isolators for optimum reliability

9-30709

AirSense Stratos Standalone Command Module

Specyfikacja techniczna

Ogólne

Sygnalizacja stanu	LED and LCD
Interfejs użytkownika	Keypad

Elektryczne

Napięcie znamionowe	21.6 to 26.4 VDC
Pobór prądu	250 mA

Wyjście

Ilość wyjść	5 - Pre-Alarm, Alarm, Alarm2, Aux Alarm (n/o) and Fault (n/c)
Typ i obciążalność wyjścia	500 mA @ 30 V

Fizyczne

Wymiary	427 x 372 x 95 mm (W x H x D)
Masa netto	5.2 kg
Kolor	Kremowy
Typ montażu	Uchwyt ścienny
Otwory kablowe	6 x M20
Materiał (pudełko)	Blacha stalowa

Środowiskowe

Temperatura pracy	-10 to +60°C (EN54-20)
Wilgotność względna	0 to 90% noncondensing
Środowisko	Wewnątrz
Szczelność IP	IP40

Będąc firmą innowacyjną, Carrier Fire & Security zastrzega sobie prawo do zmian w specyfikacji wyrobów bez uprzedzenia. W celu uzyskania najnowszych specyfikacji prosimy o wizytę na stronach pl/firesecurityproducts.com lub kontakt z przedstawicielem handlowym.

Last updated on 7 March 2024 - 11:23