



3649-0001

Pronto single-sided ID Card Printer

Single Feed for on-demand applications

The Magicard Pronto printer features single card feed that allows you to produce a personalised card on demand in moments. It offers edge to edge and sharp image quality for simple and easy card printing in a compact and highly reliable package.

Robust, compact and portable

The Magicard Pronto printer's aesthetic curves hide an ultra-robust product. Its light and compact design makes it easy to transport to any location and reside on any counter or deskstop

Intuitive features and design

Its intuitive design with a colour-coded status LED, USB interface and Microsoft certified plug and play driver, make the Pronto easy to use, set up and operate straight out of the box.

Budget friendly and secure

The Magicard Pronto printer delivers low cost printing and free card visual security with its built-in HoloKote anticounterfeiting watermark feature. A choice of 4 FREE standard watermark designs are selectable via the driver

New UltraDriver

Our user-friendly printer driver for the Magicard printers is now available in seven languages; English, Spanish, French, German, Italian, Portuguese and Chinese. UltraDriver supports Microsoft® Windows® XP, Windows 2000, Windows 2003 and Windows Vista



Details

- Edge-to-edge full colour printing
- Card Security: HoloKote and HoloPatch
- USB interface
- Dye film must be ordered separately

3649-0001

Pronto single-sided ID Card Printer

Especificações técnicas

Geral		Card Thickness	
Funcionalidade	Impressão	0.51mm to 1.6mm / 0.020" to 0.063"	
Aceita cartão de dimensões standard	CR79, CR80	Printhead	
Sistemas operativos suportados	Mac OS X, Windows 10, Windows 7, Windows 8.x, Windows Server 2003 R2, Windows Server 2008, Windows Server 2012, Windows Server 2016, Windows Vista, Windows XP	300dpi field replaceable	
Impressão		Printing technology	
Método de impressão	Direto para o Cartão	Thermal transfer with solid wax and color dye sublimation	
Laminação	Frente	Power Source	
Lado de impressão	Frente	External power supply 100 -240V 50-60 Hz autoranging	
Velocidade de impressãoK: 8, YMCK: 2 de cartões por minuto		Environment	
Série de impressora	Ultra ID	Sheltered office environment 10°C to 30°C	
Elétrica		Dimensions	
Valor da fonte de alimentação	100 to 240 VAC	270 x 215 x 233 mm (L x W x H)	
Físico		Weight	
Dimensões físicas	345 x 265 x 420 mm	4.4 kg	
Peso líquido	3735 g		
Peso do envio	4500 g		
Cor	Branco		
Ambiental			
Temperatura de operação	10 to 30°C		
Humidade relativa	20 to 80% noncondensing		
Regulamentação			
Conformidade	CE, RoHS		
Visual Security			
	Option to print a HoloKote Security watermark across the card surface		
Print Speed			
Color	35s		
Monochrome	7s		
Warranty			
	2 years limited warranty (North America and EU only). Elsewhere 1 year limited warranty		
PC Interface			
	USB rev 1.1 (USB 2.0 Compatible)		
Software Drivers			
	Windows 2000, 2003 Server, XP and Vista drivers all supplied with printer.		
Card Types			
	Prints on all standard PVC ISO CR80 sized cards. HoloPatch cards available.		