

# 9-30709

## AirSense Stratos Standalone Command Module

### Description

---

AirSense Stratos Command Module provides a single location display, control and interfacing option for systems of upto 127 detectors. Command Module allows global programming of all detector functions simultaneously.

The integral bargraph automatically displays the status of the detector with the highest alarm level to identify potential problem areas.

The PIN protected programmer enables global entry of all detector settings to significantly reduce commissioning time.

### Typical Applications

---

- Data storage units
- Prison cells
- Plant rooms
- Air conditioning units
- Equipment racks
- Computer rooms
- Air duct protection
- Heritage property protection
- Critical equipment
- Anti-smoking enforcement
- Motor rooms

### Options Available

---

- Addressable Protocol Interface Cards APIC™ available
- SenseNet compatible - up to 127 detectors per loop
- Remote Display units available
- Suitable for MatrixScan, a patented software system which provides virtual addressable location detection - e.g. 10 physical detectors would provide up to 45 unique addressable locations.



### Details

---

- RS485 communications built in as standard for networking and remote communications
- Network control of 127 detectors
- Built in Short Isolators for optimum reliability

# 9-30709

## AirSense Stratos Standalone Command Module

### Especificações técnicas

---

#### Geral

---

Indicação de estado	LED and LCD
User interface	Keypad

---

#### Elétrica

---

Tensão de operação	21.6 to 26.4 VDC
Consumo de corrente	250 mA

---

#### Saída

---

Quantidade de saídas	5 - Pre-Alarm, Alarm, Alarm2, Aux Alarm (n/o) and Fault (n/c)
Tipo de output e operação	500 mA @ 30 V

---

#### Físico

---

Dimensões físicas	427 x 372 x 95 mm (W x H x D)
Peso líquido	5.2 kg
Colour	Crema
Mounting type	Montagem em parede
Entradas para cabos	6 x M20
Materiais (caixa)	Chapa de aço

---

#### Ambiental

---

Temperatura de operação	-10 to +60°C (EN54-20)
Humidade relativa	0 to 90% noncondensing
Ambiente	Interior
Classificação IP	IP40

---



Como empresa de inovação, a Carrier Fire & Security reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite [pt.firesecurityproducts.com](http://pt.firesecurityproducts.com) online ou contate o departamento comercial.

Last updated on 7 March 2024 - 11:23