



## ACL800-PB-S

### ACL800 TOUCH CAPACITIVE PUSH BUTTON - STAND ALONE, SURFACE MOUNT, SILVER

#### Product description

---

ACL800-PB Series is a Request-To-Exit Surface mount Push Button switch, it will work independently (standalone) or can equally be connected via a controller to provide exit from a secured area (Push Button Input). It includes a buzzer and a dual LED. The ACL800-PB Series can work in pulse (3, 5, 10 sec) or latch mode.

#### The ACL800 range

---

The ACL800 Series consists of all the required elements to establish a range with a state-of-the-art design. This new range, consisting of readers, stand-alone keypad readers and Request-To-Exit touch sensitive push buttons, provides all you need for a coherent look-and-feel attractive project. Moving forward, this product range will be further developed with biometric readers.



#### Detalhes

---

- Indoor/outdoor
- Dust proof and water-resistant (IP65)
- Attractive and timeless design
- Touch Sensitive Technology
- Includes a buzzer
- Dual LED
- Work in pulse (3, 5, 10 sec) or On/Off latched mode
- Surface mount
- Backlight illumination
- Request-To-Exit Touch capacitive push button

# ACL800-PB-S

## ACL800 TOUCH CAPACITIVE PUSH BUTTON - STAND ALONE, SURFACE MOUNT, SILVER

### Especificações técnicas

#### Sistema

RTE (Pedido De Saída)	Sim
Nr. de LEDs	2
Manual de instalação de idiomas	English

#### Tecnologia

Tipo leitor	Touch
-------------	-------

#### Interface & ligações

Tipo de conector	Rabo porco
Comprimento do chicote	100 cm

#### Tipo de tamper

Tamper remoção	Não
Tamper de abertura	Sim

#### Operação

Autônoma	Sim
----------	-----

#### Elétrica

Tipo de fonte de alimentação	VDC
Valor da fonte de alimentação	5 to 24 VDC 15 to 24 VAC
Consumo de corrente	100 mA at 24 VDC Maximum 65 mA at 24 VDC Typical 65 mA at 12 VDC

#### Físico

Dimensões físicas	92 x 51 x 25 mm
Peso líquido	163 g
Peso do envio	295 g
Cor	Prata
Material	Alumínio moldado
Fator de forma	Mullion
Tipo de montagem	Montagem em superfície

#### Ambiental

Ambiente	Interior, Exterior
Temperatura de operação	-20 to +50°C
Temperatura de armazenamento	-20 to +50°C

#### Regulamentação

Conformidade	CE, RoHS
--------------	----------

#### Operation

Backlighting	Green (Door opened) - Red (Door Closed, Denied, Blocked) - Orange (Idle)
Visual and Sound signals	Complete button lighting + buzzer

#### Interface & connections

Exit	Relay 1A (NO/C/NC)
Relay Output	On/off Latched or Timed (3, 5 or 10 seconds)

#### Technology

Request to Exit	Touch Sensitive
-----------------	-----------------