



DMN700W

Botoneira Comando Branca - Contacto Seco

General

Installation efficiency, flexibility and full compliance with the latest standards are at the heart of the new MCP indoor call point range.

Installation

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

Options and approvals

Through new standards and legislation, both break glass and re-settable operating elements may now be used. To provide the greatest 'flex-ability', the new MCP range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.

Full compliance with the latest standards is essential and the new MCP indoor call point range is fully approved to the latest EN54-11 standard



Detalhes

- Enhanced aesthetics
- Easy to install (plug and play)
- Surface mount options
- Protection hinged cover with Anti-Tamper facility
- Backward compatibale
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch
- Fully approved to the latest standards

DMN700W

Botoneira Comando Branca - Contacto Seco

Especificações técnicas

Isolamento

Resistência da série	NA
----------------------	----

Físico

Peso líquido	110 g
--------------	-------

Cor	Branco
-----	--------

Materiais (caixa)	PC / ABS
-------------------	----------

Ambiental

Temperatura de operação	-10 to +55°C
-------------------------	--------------

Temperatura de armazenamento	-10 to +55°C
------------------------------	--------------

Humidade relativa	0 to 95% noncondensing
-------------------	------------------------

Ambiente	Interior
----------	----------

Classificação IP	IP24D
------------------	-------

Cable Termination

0.5 - 2.5 mm ²

Max. contact rating (resistive load)

2A @ 30 VDC

Produtos compatíveis

Categoria	Referência	Descrição
Dispositivo de deteção	DM715	Vidro Universal para Botoneira EN54 - Sem Logótipo
Dispositivo de deteção	DMN782	Cobertura Articulada Transparente para Botoneira
