



DMN700Y03-KITR

Botoneira Comando Amarela com Cobertura - Contacto Seco

General

DMN700Y03-KITR is a yellow manual call point for surface mount applications. It offers a single pole, changeover contact with common, normally open and normally closed connections. It is supplied with a resettable break glass and test key.

Installation

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

Options

Through new standards and legislation, both break glass and re-settable operating elements may now be used. To provide the greatest 'flex-ability', the new MCP range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.



Detalhes

- Enhanced aesthetics
- Easy to install (plug and play)
- Protection hinged cover with Anti-Tamper facility
- Backward compatible
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch

DMN700Y03-KITR

Botoneira Comando Amarela com Cobertura - Contacto Seco

Especificações técnicas

Isolamento

Resistência da série	NA
----------------------	----

Físico

Dimensões físicas	92 x 115 x 59 mm (W x H x D)
-------------------	------------------------------

Peso líquido	110 g
--------------	-------

Cor	Amarelo
-----	---------

Tipo de montagem	Montagem em superfície
------------------	------------------------

Materiais (caixa)	PC / ABS
-------------------	----------

Ambiental

Temperatura de operação	-10 to +55°C
-------------------------	--------------

Temperatura de armazenamento	-10 to +55°C
------------------------------	--------------

Humidade relativa	0 to 95% noncondensing
-------------------	------------------------

Ambiente	Interior
----------	----------

Classificação IP	IP24D
------------------	-------

Cable Termination

0.5 to 2.5 mm ²

Electrical

Max. contact rating (resistive load)	2 A @ 30 VDC
--------------------------------------	--------------

Produtos compatíveis

Categoria	Referência	Descrição
Dispositivo de deteção	DMN782	Cobertura Articulada Transparente para Botoneira
Dispositivo de deteção	DMN787Y	Caixa Montagem de Superfície - Amarela
Dispositivo de deteção	DMN800	Plástico de Operação por Rearme para Botoneira