

TVD-TIR6-MR-P

TruVision Dome Turret IR Camera, PAL, 600 TVL color, 3.3MM - 12.0MM Lens

Overview

The TruVision™ line includes a comprehensive family of infrared (IR) cameras for standalone or basic integrated installations that are flexible and scalable to accommodate future growth. Ideal for surveillance system installations ranging from convenience stores to retail mall parking lots, the TruVision IR line has the right cameras for your job and can help you stay within budget constraints without compromising security needs.

These flexible cameras can see in total darkness, providing color images by day and black-and-white images under IR operation in low-light applications. Form factors include omni-directional dome and traditional bullet cameras. Dome models allow for ceiling or wall mounting while still maintaining a level field of view. Single gang adaptor plates are included with the MR and HR dome models, while the bullet models offer a familiar form factor that can also be ceiling or wall mounted. TruVision IR dome and bullet cameras are also available in fixed lens and varifocal lens models.

Application

Built for long-lasting service and plug-and-play functionality, the TruVision IR line provides a valuebased solution that is ideal for applications ranging from residential to office buildings.

Designed for low-light and complete-darkness environments, TruVision cameras' balanced IR capabilities and multiple resolution options offer the perfect camera for each situation. With weather-resistant options that are well suited for indoor and outdoor applications, TruVision cameras represent sensible, secure video surveillance you can depend on.



Detalhes

- Balanced IR illumination for optimal viewing in low- to no-light environments
- provide flexible installation options and ensure the right camera for the job
- Compatible with all analog CCTV recording devices and equipment
- IP66 ratings for weather-resistant performance
- 600 TV lines

TVD-TIR6-MR-P

TruVision Dome Turret IR Camera, PAL, 600 TVL color, 3.3MM - 12.0MM Lens

Especificações técnicas

Camera


Pick-up device:	1/3 Super HAD CCD II
DSP:	SONY EFFIO-E
Total pixels:	NTSC: 811(H) x 508(V) PAL: 795(H) x 596(V)
Effective pixels:	NTSC: 768(H) x 494(V) PAL: 752(H) x 582(V)
Resolution:	600 TV lines
Sync. system:	2.1 internal
Scanning system:	NTSC 525 Lines/60 Fields; PAL 625 Lines/50 Fields
S/N ratio:	More than 50dB (AGC OFF)
Electronic shutter:	Auto 1/60 (1/50)- 1/100,000 sec.
Video output:	Composite 1.0 Vp-p / 75 ohm
IR distance:	82 ft./25 m (28 pcs IR LED)
IR trigger:	3.1 lux/3.7 lux IR ON/OFF
Lens type:	Varifocal lens: 3.5 - 12 mm
Single gang mounting plate:	Yes
Min. illumination:	0.2 lux color / F2.0; 0.00 lux IR ON

Electrical

Power source:	AC24V/DC12V
Power consumption:	5.64W (Max)
Current:	140mA (IR OFF)470mA (Max)

Environmental & Physical

Weight:	26 oz./ 0.76 kg
Dimensions:	4.69 in. (W) x 3.25 in. (H) (119 mm x 82.5 mm)
Operation temperature:	-10 to 50° C (14 to 122° F)
Storage temperature:	-20 to 70° C (-4 to 158° F)
Weather resistant:	IP66



Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.