9-30709

AirSense Stratos Standalone Command Module

Description

AirSense Stratos Command Module provides a single location display, control and interfacing option for systems of upto 127 detectors. Command Module allows global programming of all detector functions simultaneously.

The integral bargraph automatically displays the status of the detector with the highest alarm level to identify potential problem areas.

The PIN protected programmer enables global entry of all detector settings to significantly reduce commissioning time.

Typical Applications

- Data storage units
- Prison cells
- Plant rooms
- Air conditioning units
- Equipment racks
- Computer rooms
- Air duct protection
- Heritage property protection
- Critical equipment
- Anti-smoking enforcement
- Motor rooms

Options Available

- Addressable Protocol Interface Cards APIC™ available
- SenseNet compatible - up to 127 detectors per loop
- Remote Display units available
- Suitable for MatrixScan, a patented software system which provides virtual addressable location detection - e.g. 10 physical detectors would provide up to 45 unique addressable locations.

Detaljer

- RS485 communications built in as standard for networking and remote communications
- Network control of 127 detectors
- Built in Short Isolators for optimum reliability

9-30709

AirSense Stratos Standalone Command Module

Tekniska specifikationer

Allmänt

Statusindikering	LED and LCD
Användargränssnitt	Keypad

Elektrisk

Driftspänning	21.6 to 26.4 VDC
Nuvarande förbrukning	250 mA

Utgång

Utgångsmängd	5 - Pre-Alarm, Alarm, Alarm2, Aux Alarm (n/o) and Fault (n/c)
Utgångstyp och klassificering	500 mA @ 30 V

Fysisk

Fysiska dimensioner	427 x 372 x 95 mm (W x H x D)
Nettovikt	5.2 kg
Färg	Grädde
Monteringstyp	Väggmontering
Kabelinmatningar	6 x M20
Material (kropp)	Stålplåt

Miljö

Driftstemperatur	-10 to +60°C (EN54-20)
Relativ luftfuktighet	0 to 90% noncondensing
Miljö	Inomhus
IP-betyg	IP40

Carrier Fire & Security förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 7 March 2024 - 11:23