

RXI4N8

Quickbridge, 433 MHz. Fristående trådlös mottagare 8-kanaler/16 enheter. 8 fritt programmerbara utgångar. Matningsspänning 12 VDC. Självlärande

General

The "Quickbridge" Loop Receiver is a universal wireless receiver compatible with any standard hardwired control panel. Available with a wide range of wireless devices, including keyfobs, passive-infrared detectors, door/window detectors and medical panic buttons, every system can be made virtually wire-free.

The Quickbridge supports the Learn-Mode technology, which means that each device has its own factory-programmed id, so the receiver automatically recognizes each device. This dramatically reduces installation time and eliminates programming errors in the field.

Compatibility

The QuickBridge is compatible with all current Learn Mode sensors (433.92 MHz), panic button transmitters, two- and four-button keychain touchpads, with the exception of smoke detectors.



Detaljer

- 433.92 MHz Learn-Mode Technology
- Support for up to 16 wireless sensors and 45 keyfobs and panic buttons
- Monitors alarm, battery, tamper and supervisory status of transmitters
- Spatial diversity receiver with enhanced reception
- Jamming Detection
- 8 programmable zone outputs
- Zone openings and closings indication
- Non-volatile memory to prevent programming information and sensors IDs loss in case of power failure
- Compatible with all popular/current control panels

RXI4N8

Quickbridge, 433 MHz. Fristående trådlös mottagare 8-kanaler/16 enheter. 8 fritt programmerbara utgångar. Matningsspänning 12 VDC. Självlärande

Tekniska specifikationer

Allmänt

| | |
|--------------|------------------|
| Expander typ | Trådlös expander |
|--------------|------------------|

Utgångar

| | |
|-----------------|----------------------------------|
| Ombord | z1 to z8 ; Battery ; Supervision |
| Typ av utgångar | Open collector |

Trådlös

| | |
|----------------|-------------|
| Arbetsfrekvens | 433 MHz arv |
|----------------|-------------|

Elektrisk

| | |
|-----------------------|--------------|
| Driftspänning | 10 to 14Vdc |
| Nuvarande förbrukning | 60mA maximum |

Fysisk

| | |
|---------------------|---------------------------------------|
| Fysiska dimensioner | 103 x 131 x 25 mm (excluding antenna) |
|---------------------|---------------------------------------|

Miljö

| | |
|------------------|------------|
| Driftstemperatur | 0 to +40°C |
|------------------|------------|

Reglerande

| | |
|--------------|----|
| Undfallenhet | CE |
|--------------|----|

Outputs

| | |
|-------------------------|----------------------------------|
| Maximum applied voltage | 16 VDC |
| Maximum sink current | 50 mA (typical), 15 mA (minimum) |



Carrier Fire & Security förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 5 May 2023 - 10:29