

TVB-2402

TruVision HD-TVI analog bulletkamera, PAL, 720P, 2,8-12 mm optik, äkta dag/natt, DWDR, 40 m IR, dubbla utgångar 960H eller HD-TVI, koax OSD-kontroll, 12 VDC/24 VAC, IP66

Overview

The new TruVision line includes a comprehensive family of HD-TVI infrared (IR) cameras for stand-alone or integrated installations, designed for optimal image quality over existing coaxial cable.

Ideal for improving video quality of existing analog surveillance system installations ranging from convenience stores to retail mall parking lots, the TruVision HD-TVI line has the right cameras for your new or existing project and can help you stay within budget constraints without compromising security needs.

The cameras have true day/night capabilities, providing color images by day and black-and-white images under IR operation in low light applications. TruVision HD-TVI cameras are available with either fixed lens or varifocal lens.

Form factors include dome and traditional bullet cameras. Bullet models offer a familiar form factor that features a pre-installed wall mount with cable management. All models are IP66 rated for outdoor installation and select dome models are available with an IK10 vandal-rated enclosure.

All TruVision HD-TVI cameras are designed to install quickly and easily, right out of the box, so you can be up and running in no time.



Detaljer

- 720p HD resolution
- HD-TVI technology for transmitting HD quality video over existing coax cable
- True day/night functionality and infrared illuminators with Smart IR function for capturing images in various lighting scenarios
- IR range of up to 40 m
- IP66 environmental rating
- Digital wide dynamic range
- 2.8 to 12 mm lens
- Dual power 12 VDC / 24 VAC
- Bracket included
- Provide OSD control via TruVision up the coax and built-in menu button

TVB-2402

TruVision HD-TVI analog bulletkamera, PAL, 720P, 2,8-12 mm optik, äkta dag/natt, DWDR, 40 m IR, dubbla utgångar 960H eller HD-TVI, coax OSD-kontroll, 12 VDC/24 VAC, IP66

Tekniska specifikationer

Allmänt

Teknik	HD-TVI analog
Videostandard	PAL

Kamera

Sensorstorlek	1/3"
Max. upplösning	720p
Sensorsökning	Progressive
Sensortyp	CMOS
Totalt antal pixlar (H x V)	1305 x 1049
Effektiva pixlar (H x V)	1305 x 1049
Digital S/N-förhållande	More than 62 dB
Slutartid	1/25 to 1/50,000 s

Ljusprestanda

WDR-typ	Digital WDR
Digital brusreducering	3D DNR
Dag natt	True Day/Night
Motoriserat IR-skärfilter	Ja
Färgkänslighet	0.01 Lux @ (F1.2, AGC ON), 0.014 Lux @
S / V-känslighet	0 Lux with IR on
Infraröd (IR)	Ja
IR-intervall	40m

Lins

Objektivtyp	Varifokal
Brännvidd	2.8 - 12 mm @ F1.4

Nätverk

Integration	CGI, ONVIF, PSIA
-------------	------------------

Elektrisk

Driftspänning	12 VDC / 24 VAC
Energiförbrukning	12 VDC: max. 4 W / 24 VAC: max. 6W
Nuvarande förbrukning	12 VDC: max. 0.33A / 24 VAC: max. 0.25A

Fysisk

Fysiska dimensioner	105 x 94.7 x 301.4mm (4.13 x 3.74 x 11.86 in.)
Nettovikt	1075 g
Färg	Grå
Form Factor	Kula

Miljö

Miljö	Utomhus
Driftstemperatur	-30 to +60 °C (-22 to +140 °F)
Lagringstemperatur	-20 to +70° C (-4 to +158° F)
IP-betyg	IP66

Reglerande

Undfallenhet	C-tick, CE, FCC, REACH, RoHS, UL, WEEE
--------------	--

Kamera

Sync. system	Internal
Video output	Dual HD-TVI or 960H
OSD	Built-in OSD button, TruVision Coax OSD control on both HD-TVI and 960H



Carrier Fire & Security förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 24 January 2024 - 16:10