

TVB-2403

TruVision HD-TVI analog bulletkamera, PAL, 1080P, 3,6 mm optik, äkta dag/natt, WDR, 20 m IR, dubbla utgångar 960H eller HD-TVI, koax OSD-kontroll, 12 VDC, IP66

Overview

The new TruVision line includes a comprehensive family of HD-TVI infrared (IR) cameras for stand-alone or integrated installations, designed for optimal image quality over existing coaxial cable.

Ideal for improving video quality of existing analog surveillance system installations ranging from convenience stores to retail mall parking lots, the TruVision HD-TVI line has the right cameras for your new or existing project and can help you stay within budget constraints without compromising security needs.

The cameras have true day/night capabilities, providing color images by day and black-and-white images under IR operation in low light applications. TruVision HD-TVI cameras are available with either fixed lens or varifocal lens.

Form factors include dome and traditional bullet cameras. Bullet models offer a familiar form factor that features a pre-installed wall mount with cable management. All models are IP66 rated for outdoor installation and select dome models are available with an IK10 vandal-rated enclosure.

All TruVision HD-TVI cameras are designed to install quickly and easily, right out of the box, so you can be up and running in no time.



Detaljer

- 1080p HD resolution
- HD-TVI technology for transmitting HD quality video over existing coax cable
- True day/night functionality and infrared illuminators with Smart IR function for capturing images in various lighting scenarios
- IR range of up to 20 m
- IP66 environmental rating
- Wide dynamic range
- 3.6 mm fixed lens
- 12 VDC
- Bracket included
- Provide OSD control via TruVision up the coax and built-in menu button

TVB-2403

TruVision HD-TVI analog bulletkamera, PAL, 1080P, 3,6 mm optik, äkta dag/natt, WDR, 20 m IR, dubbla utgångar 960H eller HD-TVI, koax OSD-kontroll, 12 VDC, IP66

Tekniska specifikationer

Allmänt

Teknik	HD-TVI analog
Videostandard	PAL

Kamera

Sensorstorlek	1/3"
Max. upplösning	1080p
Sensorsökning	Progressive
Sensortyp	CMOS

Ljusprestanda

Dag natt	True Day/Night
Motoriserat IR-skärfilter	Ja
Infraröd (IR)	Ja

Lins

Objektivtyp	Fast
-------------	------

Nätverk

Integration	CGI, ONVIF, PSIA
-------------	------------------

Elektrisk

Strömförsörjningstyp	12 VDC
----------------------	--------

Fysisk

Färg	Grå (Pantone 428c)
Form Factor	Kula

Miljö

Miljö	Utomhus
-------	---------

Reglerande

Undfallenhet	C-tick, CE, FCC, REACH, RoHS, UL, WEEE
--------------	--



Carrier Fire & Security förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 24 January 2024 - 16:12