

TVN-2264P-4T

TruVision NVR 22P, H.265, 64 kanaler IP, 2 gigabitportar, 4 TB

Overview

TruVision NVR 22P (TVN 22) is a robust high performance H.264/H.265 network video recorder. With a total bandwidth of 256 Mbps (16-channel) or 320Mbps (32- and 64 channel) available, the TVN 22P is able to connect up to 16/32/64 IP cameras and provide real time recording (25/30 fps) at Full HD 1080p resolution on all channels simultaneously. With its fully flexible bandwidth allocation, the TVN 22P allows recording resolutions up to 8MPX at various frame rates.

Ease of use

TVN 22P was designed to make system configuration and overall use easier for both the installer and end-users through features such as: ezDDNS, start-up wizards, plug & play hard drives, auto discovery of natively supported cameras and is fully compatible with TruVision Navigator (as of 6.0SP1) and TVRmobile.

H.265

The TVN 22P is supporting both H.264 and H.265 compression techniques. The H.265 compression is the next evolution of video encoding. Using H.265 will result in a reduced file size for the same video content and a reduced transmission bandwidth compared to H.264. This means that for the same storage capacity more video can be stored when using H.265 than H.264 encoding. To use the H.265 encoding in the TVN 22, TruVision H.265 cameras need to be used.

Ease of use

Thanks to its 2U housing, the maximum on-board storage capacity for the TVN 2264P is 64 TB, using eight 8 TB hard drives. The hard drives can be accessed via the lockable front panel door, allowing customers to easily expand storage as their system and/or requirements grow. Additionally, TVN 22P supports RAID 0,1, 5, 6, 10 for storage redundancy. The supported RAID levels depend on the number on hard drives. Recording options include continuous, event and alarm. The three modes can be combined, to ensure that the most efficient recording is possible.

Basic intrusion integration

TVN 22P has an alarmreceiver module embedded inside. The alarm message receiver can connect to up to three Interlogix IP intrusion panels that report in SIA or XSIA format.

Alarm messages, disarming and arming messages can be send from the alarm panel to the recorder, which then can take actions (trigger alarm recording, send a PTZ to a preset, run a shadow tour or preset tour, trigger an alarm output or send a notification message to TVRmobile). Also the heartbeat message between panel and recorder is monitored. This solution offers straightforward alarm verification and is free of charge.



Detaljer

- Linux embedded Play and Play configuration
- Up to 320 Mbps camera recording bandwidth
- Up to 64 IP channels
- Up to 64TB embedded storage (8x 8TB)
- RAID 0, 1, 5, 6, 10 support (depending on the number of HDDs used)
- Flip-open front panel for easy HDD access, servicing & expansion
- New icon based front panel
- Real-time Full HD recording
- Motion detection, VCA, privacy masking, tamper detection
- TruVision IP camera auto-discovery
- Third party camera support via ONVIF and PSIA
- IP camera configuration import/export
- Custom protocol configuration (RTSP streaming)
- Network redundancy
- Integration of Carrier IP intrusion panels via SIA/XSIA reporting
- Recorder failover functionality (one failover unit per 4 operational recorders)
- TVK-800 IP Keypad support (no support for local display of H.265 cameras)
- USB DVD burner support
- Full browser-, OSD- and software-based access for live, recorded & configuration
- TVRmobile app for Android and iOS
- TruVision Navigator license-free client/host or standalone application

TVN-2264P-4T

TruVision NVR 22P, H.265, 64 kanaler IP, 2 gigabitportar, 4 TB

Tekniska specifikationer

Allmänt

| | |
|----------------------------|-----|
| Teknik | IP |
| Monterbar på rack | Ja |
| Rackstorleksstorlek | 2 U |
| Avtagbar fläkt | Nej |
| Redundant strömförsörjning | Nej |

Video-/ljudingång

| | |
|------------------------|------------------------------------|
| Kamerakanaler | 64 |
| Stödda videokomprimeri | H.264, H.265, MPEG-4 ngsstandarder |

Støttede standarder for videostreaming Onvif, PSIA, RTSP, RTSP Custom Protocols

Lokal översikt

| | |
|-----------------------------|-----|
| HDMI-utgång | 2 |
| HDMI-version | 2.0 |
| VGA-utgång | 2 |
| BNC-utgång | 1 |
| Max. lokal utdataupplösning | 4K |

Fjärrövervakning

Programvarukompatibilitet Advisor Management Software (ATS8600), et TruVision Navigator, TVRmobile, Web Browser

Webbläsarkompatibilitet Google Chrome, Internet Explorer, Mozilla Firefox, Safari

Lagring

| | |
|-------------------------------|---|
| Lagringskapacitet | 4 TB |
| Maximal inspelningsupplösning | 12 MP |
| Inspelningslägen | Alarm, Event, Manual, Time-lapse high, Time-lapse low |
| Extern lagring | eSATA, NAS, SAN |
| Supported RAID levels | RAID 0, RAID 1 |
| Harddiskredundans | Ja |
| Harddiskgruppering | Ja |
| SAS förlängning | Nej |
| Vänd öppen frontpanel | Ja |
| Automatisk arkivering | Ja |
| Hot reservinspelare | Ja |
| Edge failover-inspelning | Ja |

Nätverk

| | |
|------------|---|
| NIC-typ | RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface |
| NIC-läge | Network Redundancy |
| DNS-stöd | DDNS, ezDDNS, Ingen IP |
| HTTPS-stöd | Ja |

Externa gränssnitt

| | |
|---------------------------|--------|
| USB-gränssnitt tillbaka | 1 |
| USB-gränssnitt fram | 2 |
| Seriellt gränssnitt | RS-232 |
| Larmgångar | 16 |
| Larmutgångar | 4 |
| Max. analoga ljudutgångar | 1 |

Elektrisk



| | |
|----------------------|------------------|
| Strömförsörjningstyp | 100 till 240 VAC |
|----------------------|------------------|

Fysisk

| | |
|------|-------|
| Färg | Svart |
|------|-------|

Reglerande

| | |
|--------------|---------------------|
| Undfallenhet | CE, REACH, RoHS, UL |
|--------------|---------------------|



Carrier Fire & Security förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 29 February 2024 - 9:32