

TVP-2401

TruVision HD-TVI analog PTZ, PAL, 1080P, 30X, DWDR, väggmontering, CVBS & TVI dubblar utgångar, TVI/RS485/RS422-kontroll, 24 VAC, IP66

Overview

The TruVision HD-TVI Analog PTZ Cameras by Interlogix® utilize the latest PTZ technology to provide powerful, cost-effective surveillance for retail, commercial and small business applications. With 1080p resolution and a 30X optical zoom (16X digital) working together, these cameras deliver crisp, clear images, even at a distance.

With advanced features, such as True Day/Night surveillance and Digital Wide Dynamic Range (DWDR) imaging, these cameras provide optimal image quality in a variety of indoor or outdoor environments. HD-TVI Analog PTZ cameras are easy to change, with wall, pendant, surface or flush mounting options to meet various application needs.

These cameras are also fully programmable, with up to 256 presets, 8 preset tours, and shadow tours for end-user customization and flexibility. A 24-zone privacy-mask feature allows these cameras to block out sensitive areas, such as fitting rooms, or restricted areas. Motion detection, auto tracking, privacy masking and electronic image stabilization add substantial value and enhanced security to any surveillance system.



Detaljer

- 1/3" Progressive Scan CMOS
- 1080p resolution
- Dual output HD-TVI and 960H BNC
- HD-TVI technology for transmitting full HD-quality video over existing coax cable
- 24 Privacy Masks
- Models include 2 alarm inputs and 1 relay output
- 256 preset positions, 8 preset tours, and 4 shadow tours
- 360° Endless Rotation
- 250°/s Pan Preset Speed and 300°/s Tilt Preset Speed
- Auto-Flip image
- Compatible with GEA and UVP accessories
- Wall bracket to be ordered separately
- EIS (Electronic Image Stabilization)

TVP-2401

Truvision HD-TVI analog PTZ, PAL, 1080P, 30X, DWDR, väggmontering, CVBS & TVI dubblar utgångar, TVI/RS485/RS422-kontroll, 24 VAC, IP66

Tekniska specifikationer

Allmänt

Teknik	HD-TVI analog
Videostandard	PAL
Videoutgång	HD-TVI

Kamera

Sensorstorlek	1/3"
Max. upplösning	1080p
Sensorsökning	Progressive
Sensortyp	CMOS

Ljusprestanda

WDR-typ	Digital WDR
Dag natt	True Day/Night
Motoriserat IR-skärfilter	Ja
Infraröd (IR)	Nej

Lins

Objektivtyp	Varifokal motoriserad
Objektivfäste	Camera Block
Auto iris	Ja
Auto fokus	Ja
Motoriserat zoom	Ja

Pan / tilt / zoom

Vänd automatiskt	Ja
Optisk zoom	30x
Digital zoom	16x
PTZ-protokoll som stöds	AD_CODE, BOSCH_CODE, Interlogix RS-485, Pelco-D, Pelco-P

Larm I/O

Larmingångar	2
--------------	---

Lagring

Lokalt lagringsstöd	No
---------------------	----

Video intelligens

Larmutlösare	Motion detection, Privacy Masking, Video tampering
Smart event	Defog, Electronic Image Stabilization (EIS)
Intelligent spårning	Nej

Elektrisk

Strömförsörjningstyp	24 VAC
----------------------	--------

Fysisk

Färg	Grå
Form Factor	PTZ
Montera	Pendant mount (requires additional accessory), Wall mount (requires additional accessory)

Miljö



Vandalsäker	Ja
Påverkan	IK10
Miljö	Utomhus

Reglerande

Undfallenhet	CE, FCC, HALT, REACH, RoHS, UL, WEEE
--------------	--------------------------------------

Kompatibla produkter

Kategori	Referens	Beskrivning
Strömförsörjning	ATD-6814-PSU	Power supply unit for dome cameras and fixed cameras, 24 VAC, 4 Amps



Unit: mm



Carrier Fire & Security förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 26 January 2024 - 10:13